

Ivan Valbusa

The
biblatex-philosophy
bundle

v1.1 – 2015/06/13

Copyright © 2009-2015 Ivan Valbusa.

This package is author-maintained. Permission is granted to copy, distribute and/or modify this software under the terms of the LaTeX Project Public License, version 1.3c or later (<http://latex-project.org/lppl>). This software is provided "as is", without warranty of any kind, either expressed or implied, including, but not limited to, the implied warranties of merchantability and fitness for a particular purpose.

If you have any questions, feedback or requests please email me at `ivan dot valbusa at univr dot it`. If you need specific features not already implemented, remember to attach the example files.

User’s Guide to biblatex-philosophy

Bibliography styles for (Italian) users of biblatex

v1.1 – 2015/06/13

Ivan Valbusa

Dipartimento di Filologia, Letteratura e Linguistica
Università degli Studi di Verona
ivan dot valbusa at univr dot it

Abstract

This package provides a small collection of bibliography and citation styles for use with Philipp Lehman’s `biblatex` package. These styles aim to match the needs of the Italian writers, particularly those concerned in the humanities (for example the comma is used to distinguish the units of the entry). They offer some useful features to compose detailed bibliographic entries including the translation data of foreign texts, annotations etc. Many options allow you to change the style defaults. Only the Italian, English and Spanish localization is available for now but you can use the styles with all the languages supported by `babel` (or `polyglossia`) adding simple redefinitions.

Contents

1	Use	4	4.2.1	philosophy-classic																																																																
				and philosophy-modern	12																																																															
2	The styles	5	4.2.2	philosophy-verbose	12																																																															
2.1	philosophy-classic	5																																																																		
2.2	philosophy-modern	5	5	Customizations	12																																																															
2.3	philosophy-verbose	6	3	Specialities	6	5.1	Fonts	12	3.1	Related entries	6	5.2	Punctuation	13	3.2	Classical works	7	5.3	Lengths	13	3.3	Crossreferences	8	5.4	Languages	13	3.4	Annotated entries	8	5.5	Date and page ranges	14	3.5	Citation commands	9	6	Backward compatibility	14	4	Options	9	6.1	Deprecated fields	14	4.1	Global	9	6.2	Deprecated options	16	4.2	Style-specific	12	7	The Code	19				7.1	philosophy-standard.bbx	19				7.1.1	Global options	19
3	Specialities	6	5.1	Fonts	12																																																															
3.1	Related entries	6	5.2	Punctuation	13																																																															
3.2	Classical works	7	5.3	Lengths	13																																																															
3.3	Crossreferences	8	5.4	Languages	13																																																															
3.4	Annotated entries	8	5.5	Date and page ranges	14																																																															
3.5	Citation commands	9	6	Backward compatibility	14																																																															
4	Options	9	6.1	Deprecated fields	14																																																															
4.1	Global	9	6.2	Deprecated options	16																																																															
4.2	Style-specific	12	7	The Code	19																																																															
			7.1	philosophy-standard.bbx	19																																																															
			7.1.1	Global options	19																																																															

7.1.2	Name format	21	7.3.5	Internal commands for crossreferences	57
7.1.3	New internal commands	21	7.3.6	The <code>restoreclassic</code> option	58
7.1.4	Fields formats	22	7.4	<code>philosophy-verbose.bbx</code> .	59
7.1.5	The <code>orig-</code> macros (deprecated)	24	7.4.1	Initial settings	59
7.1.6	New macros	26	7.4.2	Internal commands for crossreferences	60
7.1.7	The <code>related</code> field mechanism	31	7.5	<code>philosophy-classic.cbx</code> .	64
7.1.8	Bibliography drivers .	32	7.5.1	Initial settings	64
7.2	<code>philosophy-classic.bbx</code> .	51	7.5.2	Author-title macros . .	65
7.2.1	Initial settings	51	7.5.3	Author-year macros .	66
7.2.2	New macros	52	7.5.4	Citation commands . .	69
7.2.3	Internal commands for crossreferences	54	7.6	<code>philosophy-modern.cbx</code> . .	70
7.2.4	The <code>nodate</code> option . .	55	7.7	<code>philosophy-verbose.cbx</code> .	71
7.3	<code>philosophy-modern.bbx</code> . .	55	7.7.1	Initial settings	71
7.3.1	Initial settings	55	7.7.2	New macros	72
7.3.2	New lengths	55	7.7.3	Citation commands . .	74
7.3.3	New commands	55	7.8	<code>italian-philosophy.lbx</code> .	74
7.3.4	New macros	56	7.9	<code>english-philosophy.lbx</code> .	75
			7.10	<code>spanish-philosophy.lbx</code> .	75

A brief history

The first step toward the creation of the `philosophy-modern` style was the request of Lorenzo Pantieri in the G_UIT Forum: <http://www.guit.sssup.it/phpbb/viewtopic.php?t=6472> (See the discussion on <http://www.guit.sssup.it/phpbb/viewtopic.php?t=6717..>) Now this is the bibliography style of *L’arte di scrivere con L^AT_EX*, the most popular Italian guide to L^AT_EX (Pantieri and Gordini 2011).

I would like to thank who took part in the debate on G_UIT Web site and the authors of the styles which inspired `biblatex-philosophy`, specifically: Dominik Waßenhoven (2011), James Clawson (2010) and Sander Gliboff (2010).

1 Use

The styles can be loaded as usual. To ensure Italian-style quotation marks, you need to call the `babel` and `csquotes` packages in the preamble of your L^AT_EX document:

```
\usepackage[italian]{babel}
\usepackage[style=italian]{csquotes}
\usepackage[style=philosophy-<style>,backend=biber]{biblatex}
\addbibresource{<bibfile>.bib}
```

Replace `<style>` with `classic`, `modern` or `verbose`, and `<bibfile>` with the name of your bibliography file (“.bib” must be declared). See the example files in the `texmf-dist/doc/latex/biblatex-philosophy/examples.zip` folder.

To uniform the style of quotation marks in multilingual bibliographies typeset using the `babel=other` package option, you can use the `\DeclareQuoteAlias` command:

```
\DeclareQuoteAlias{italian}{german}
```

The philosophy styles require `biber` so remember to configure your editor to use it. If you prefer `bibtex` you have to declare it with the `backend=bibtex` option but some bibliography drivers will not work properly.

2 The styles

2.1 philosophy-classic

The `classic` style is a standard author-year style associated to a compact citation scheme which allows to cite multiple entries of the same author and/or published in the same year, omitting some redundant informations:

Knuth (1984, 1986a,b,c,d)

- Donald E. Knuth (1984-1986), *Computers & Typesetting*, 5 vols., Addison-Wesley, Reading, Mass.
- (1984) *Computers & Typesetting*, vol. A: *The TeXbook*, Addison-Wesley, Reading, Mass.
 - (1986a) *Computers & Typesetting*, vol. B: *TeX: The Program*, Addison-Wesley, Reading, Mass.
 - (1986b) *Computers & Typesetting*, vol. C: *The METAFONTbook*, Addison-Wesley, Reading, Mass.
 - (1986c) *Computers & Typesetting*, vol. D: *METAFONT: The Program*, Addison-Wesley, Reading, Mass.
 - (1986d) *Computers & Typesetting*, vol. E: *Computer Modern Typefaces*, Addison-Wesley, Reading, Mass.

2.2 philosophy-modern

The `philosophy-modern` style uses the `philosophy-classic` style for the citations but produces a fancy bibliography divided into blocks, which is particularly suited for bibliographies with many entries for the same author:

Donald E. Knuth

- 1984/1986 *Computers & Typesetting*, 5 vols., Addison-Wesley, Reading, Mass.
- 1984 *Computers & Typesetting*, vol. A: *The TeXbook*, Addison-Wesley, Reading, Mass.
- 1986a *Computers & Typesetting*, vol. B: *TeX: The Program*, Addison-Wesley, Reading, Mass.
- 1986b *Computers & Typesetting*, vol. C: *The METAFONTbook*, Addison-Wesley, Reading, Mass.
- 1986c *Computers & Typesetting*, vol. D: *METAFONT: The Program*, Addison-Wesley, Reading, Mass.

2.3 philosophy-verbose

This style is aimed for citations given in the footnotes and follows the most popular scheme used in the Italian humanities.

It prints a full citation similar to a bibliography entry when an item is cited for the first time, and a short citation afterwards, using the title (possibly shortened in the `shorttitle` field), followed by the string “cit.”. Citing the same entry two times, in the second one the string “Ivi” is used; citing the same place of the previous citation you will have “*Ibidem*”:

¹ Cfr. Cartesio, *Discorso sul metodo*, trad. e introd. di Lucia Urbani Ulivi, 1^a ed., testo francese a fronte, Bompiani, Milano 2002, p. 43.

² Ivi, p. 26.

³ *Ibidem*.

⁴ Settimo Termini, «Vita morte e miracoli di Alan Mathison Turing», in *Vite matematiche. Protagonisti del '900 da Hilbert a Wiles*, a cura di Claudio Bartocci *et al.*, Springer-Verlag Italia, Milano 2007, pp. 59–61.

⁵ Cartesio, *Discorso sul metodo* cit., p. 35.

When there is only one entry for the same author, with the `singletitle=true` option the string “op. cit.” is used instead of the (short) title followed by “cit.”:

⁶ Cartesio, op. cit., p. 35.

All the scholarly abbreviations (*latinitates*) but “cit.” are printed by default in normal font. With the `latinemph` option (section 4.2.2) you can get them in italic shape.

3 Specialities

The first simple and trivial characteristic of these style is that they use commas instead of dots to separate the parts of the entry, according to the most common Italian tradition. But they do much more, of course.

3.1 Related entries

The philosophy styles use the mechanism provided by the `related` field to typeset complex entries comprising both the original publication data and the translation data (see Poincaré 1968). Previous versions of the styles provided a different mechanism to manage translations. This feature is now deprecated and it is still supported only for backward compatibility. See section 6.1 for details.

Jules-Henri Poincaré (1968), *La science et l'hypothèse*, Flammarion, Paris; trans. as *La scienza e l'ipotesi*, ed. by Corrado Sinigaglia, Bompiani, Milano 2003.

```
@book{Poincare:1968-ORIG,
  author    = {Jules-Henri Poincaré},
  title     = {La science et l'hypothèse},
  publisher = {Flammarion},
  location  = {Paris},
  date      = {1968},
  related   = {Poincare:1968-ITA}}
```

```
@book{Poincare:1968-ITA,
  author    = {Jules-Henri Poincaré},
  editor    = {Corrado Sinigaglia},
  title     = {La scienza e l'ipotesi},
  publisher = {Bompiani},
  location  = {Milano}}
```

Since Biber 1.6 you can have cascading relations too (see Popper 1934).

```
@Book{key1,
  ...
  related = {key2},
  ...
}

@Book{key2,
  ...
  related = {key3},

}

@Book{key3,
  ...
}
```

The related entry is preceded by the `translationas` string which defaults to “trad. it.” for Italian documents and “trans. as” for English documents. If you want to change it, use the `relatedstring` field. For example:

```
@book{Poincare:1968-ORIG,
  author      = {Jules-Henri Poincaré},
  ...
  related     = {Poincare:1968-ITA},
  relatedstring = {ed.~it.}}
```

3.2 Classical works

The treatment of the classical works and other writings with uncertain or omitted date is particularly difficult and inevitably imposes some choices.

If there is a critical edition you should cite it directly, such as Heidegger (2001). If you do not like this anachronistic label you may use the `shorthand` field, such as Kant (1968b [henceforth cited as KpV]). Note that a “shorthand intro” is automatically printed when the entry is cited for the first time and omitted afterwards. To turn off this capability load the option `shorthandintro=false`. In this case you will need a list of shorthands (`\printshorthands` command). If you do not like these solutions you can use the `entrysubtype` field with `classic` value (see section 3.2) or the `\sdcite` command (section 3.5).

nameaddon field (literal)

An addon to be printed immediately after the author name in the bibliography. It is useful for those author known with alias, Latinized names, etc. (see Komensky 1969).

entrysubtype field (literal)

This feature is active only for the `classic` and `modern` styles. With the `classic` value the citation commands will produce an author-title label. This is useful for citing works from classical antiquity, such as Aristotle, *Physics*:

```
@book{aristotle:physics,
  entrysubtype = {classic},
  author       = {Aristotle},
  title        = {Physics},
  ...
}
```

In the bibliography the entry is printed with the author-year label, but with the `skipbib` option in the `options` field you can exclude it from the bibliography.

3.3 Crossreferences

The `philosophy` styles allow you to manage entries referring to other entries through the `crossref` fields. This is very useful when you have to cite two or more `@incollection` of the same `@collection` (see Corrocher 2009; Federspil and Vettor 2009). In this way the `@collection` is printed in the bibliography and is cross-referenced inside the `@incollection`, using the corresponding author-year label (the mechanism is the same for `@inbook` items).

When you have to cite only one `@incollection` of a single `@collection` you have three choices:

1. use the `crossref` field (see Rossitto 1977; Termini 2007). In this case all the `@collection` data are automatically printed inside the `@incollection` entry;
2. put the `@collection` data in the fields of the `@incollection` entry (see Valbusa 2007). In this case the `@incollection` is self-contained;
3. put the `@collection` data in the fields of the `@incollection` entry and put the `@collection` label in the `xref` field of the `@incollection` (see Kant 1968c,d).

With the `verbose` style, when citing `@incollections` entries, the data of the `@collection` are printed entirely in the first citation and shortened afterwards. Anyway in the final bibliography the `@incollection` is always complete of all the informations about the corresponding `@collection`.

3.4 Annotated entries

library field (literal)

This field is printed at the end of the entry, in a new period. It is aimed for secondary informations such as the location of the texts, historical notes, etc. (see Heidegger 2001).

annotation/annotate field (literal)

This field is printed in a new paragraph at the very end of the entry. It requires the `annotation` package option. The default font can be changed redefining the `\annotationfont` command (section 5.1). See the examples in the references of this documentation.

3.5 Citation commands

`\sdcite{<key>}`

Uses an author-title label instead of an author-year label (defined only for the `classic` and `modern` styles). It is useful for some classical or undated works (see section 3.2). Writing `\sdcite[15]{guzman:sd}` you will obtain: Guzmán de Rojas, *Problemática*. This command is deprecated. Use the `entrysubtype` field instead (see section 3.2).

`\footcitet{<key>}`

Same as `\footcite`,^a but with the `\textcite` style.^b (defined only for the `classic` and `modern` styles).

^aCorrocher 2009, pp. 12–13.

^bCorrocher (2009, pp. 12–13).

`\ccite{<key>}`

The same as `\cite`, but omits the author’s (editor’s) name (defined only for the `verbose` style). Here is an example:

This topic is discussed in `\cite{Rossi:2007}` and in the recent
`\ccite{Rossi:2008}`.

This topic is discussed in P. Rossi, *History of Types*, La TeXnica, Verona 2007 and in the recent *Types of History*, Typographica, Milano 2008.

4 Options

4.1 Global

`relatedformat=semicolon, parens, brackets` default: `semicolon`

`semicolon` The “related” entry is preceded by a semicolon.

`parens` Puts the “related” entry in parentheses.

`brackets` Same as the previous option but with brackets.

`shorthandintro=true, false` default: `true`

`true` Prints a language-specific expression such as “hence- forth cited as [`<shorthand>`]” to introduce shorthands on the first citation. You can overwrite the default expression using the `shorthandintro` field. Note that the alternative expression must include the shorthand.

Kant (1968a [henceforth cited as KpV])

false Does not print the intro to the shorthand. Obviously, this option requires a list of shorthands (\printshorthand command).

scauthors=true, false default: **false**

Prints the names (author, editor, etc.) at the beginning of the entry in small caps shape, both in citations and in bibliography:

If you want *all* the names (translator, commentator, etc.) in small caps, you have to redefine the \mkbibname... commands (see biblatex documentation for details).

scauthorsbib=true, false default: **false**

Same as the previous, but only for the bibliography.

scauthorscite=true, false default: **false**

Same as the previous, but only for the citations.

lowscauthors=true, false default: **false**

Prints the initials of the names in lowercase small capitals. For example you will obtain DONALD E. KNUTH instead of DONALD E. KNUTH. If you need the uppercase for some specific entries use the \MakeUppercase command.

publocformat=publocyear, locpubyear, loccolonpub default: **publocyear**

This option provides three styles for typesetting the “publisher/location/date” block. It is active also for the related entry (see above) and for the orig-fields (see section 6.1).

publocyear Oxford University Press, Oxford 2007

locpubyear Oxford, Oxford University Press, 2007

loccolonpub Oxford: Oxford University Press, 2007

volnumformat=strings, parens, plain default: **plain**

This option provides three styles for typesetting the “volume/number” block in @article entries.

plain ... *Journal Title*, 5, 8, ...

strings ... *Journal Title*, vol. 5, n. 8, ...

parens ... *Journal Title* (5, 8), ...

You can combine this option with `volumefORMAT` options and re-defining the `\volnumPUNCT` command you can get other styles (see section 5.3):

```
... Journal Title, 5/8, ...
... Journal Title, V/8, ...
... Journal Title (5/8), ...
... Journal Title (V/8), ...
```

`volumefORMAT=arabic, roman, romansc, Roman`

default: `arabic`

This option provides three styles for typesetting the `volume` field:

<code>arabic</code>	... <i>Book Title</i> , vol. 12, ...
<code>roman</code>	... <i>Book Title</i> , vol. xii, ...
<code>romansc</code>	... <i>Book Title</i> , vol. XII, ...
<code>Roman</code>	... <i>Book Title</i> , vol. XII, ...

With the command

```
\DeclareFieldFormat{volume}{\bibstring{volume}~#1}
```

you can restore the default format for all but `@article` entries.

`editionFORMAT=arabic, roman, romansc, Roman`

default: `arabic`

This option provides three styles for typesetting the `edition` field:

<code>arabic</code>	... <i>Book Title</i> , 3 ^a ed., ...
<code>roman</code>	... <i>Book Title</i> , iii ed., ...
<code>romansc</code>	... <i>Book Title</i> , III ed., ...
<code>Roman</code>	... <i>Book Title</i> , III ed., ...

`inbeforejournal=true, false`

default: `false`

Prints the string “in” before the `journaltitle` in the `@article` entries.

`annotation=true, false`

default: `false`

Shows the `annotation` field, only in the bibliography (see also section 3.4).

`library=true, false`

default: `true`

Shows the `library` field, both in the bibliography and in the citations (see also section 3.4).

`classical=true, false`

default: `false`

[only for Italian and Spanish documents] It requires `babel` or `polyglossia`.

If `true` it doubles the last consonant of the abbreviations such as “p.”, “vol.”, “col.” etc. when used in the plural form. For example you will have “p.” for “page” and “pp.” for “pages”. This habit is very common in Italian writings even if it remains useless.

4.2 Style-specific

4.2.1 philosophy-classic and philosophy-modern

`square=true, false` default: `false`

Uses brackets instead of parentheses in the citations and in the author-year label used in the bibliography.

`nodate=true, false` default: `true`

Prints the `nodate` string when `year` or `date` is missing.

`yearleft=true, false` default: `false`

[philosophy-modern only]

Prints the date flushed left in the bibliography.

`restoreclassic=true, false` default: `true`

[philosophy-modern only]

This option can be given as an optional argument of `\printbibliography`:

`\printbibliography[restoreclassic]`

It restores the `classic` style in a document typeset using the `modern` style. It is useful to compose a “Web List” like that at the end of this document (active only for the `philosophy-modern`).

4.2.2 philosophy-verbose

`latinemph=true, false` default: `false`

Prints the *latinitates* “*ivi*” and “*ibidem*” in italic shape.

`commacit=true, false` default: `false`

Adds a comma at the end of the `shorttitle` field when this is followed by the string `cit.`: “*Descartes, Discours de la méthode, cit.*”.

5 Customizations

5.1 Fonts

`\annotationfont{<code>}` default: `\footnotesize`

The font of the annotation field. It can be redefined with:

`\renewcommand*{\annotationfont}{\normalsize\sffamily}`

`\libraryfont{(code)}` default: `\normalfont`

The font of the `library` field. It can be redefined with:

```
\renewcommand*\libraryfont{\sffamily}
```

5.2 Punctuation

`\volnumpunct{(code)}` default: `\addcomma\space`

The separator between `volume` and `number` in `@article` entries. It can be redefined with:

```
\renewcommand*\volnumpunct{/}
```

5.3 Lengths

The new lengths described in this section are defined only for the `modern` style. For the other customizable lengths see the `biblatex` documentation (Lehman 2011).

`\postnamesep` The space between author (or editor) and the first entry relating to him.

`\yeartitle` The space between year and title.

The `modern` style redefines also the following `biblatex` lengths:

`\bibnamesep` The vertical space between two blocks of authors.

`\bibitemsep` The vertical space between the individual entries in the bibliography.

`\bibhang` The hanging indentation of the bibliography.

These are the default values for the lengths used by the `modern` style:

```
\setlength{\yeartitle}{0.8em}
\setlength{\postnamesep}{0.5ex plus 2pt minus 1pt}
\setlength{\bibitemsep}{\postnamesep}
\setlength{\bibnamesep}{1.5ex plus 2pt minus 1pt}
\setlength{\bibhang}{4\parindent}
```

If you want to change them past these codes in the preamble of your document and modify the values according to your needs.

5.4 Using the styles with other languages

The languages currently supported by this package are Italian, English and Spanish.

In order to use the styles with different languages, you have to define in the preamble of your document all the string not defined in the localization file of the language loaded. This is a sample code for using the styles in german documents:

```
\NewBibliographyString{edorig,cit}
\DefineBibliographyStrings{german}{%
  inherit      = {german},
  translationas = {deut\addotspace \"Ubers\adddot},
  edorig       = {...},
  cit          = {...},
  reviewof     = {...}}
```

Another approach is to use the \DeclareLanguageMapping command. See the documentation of the biblatex package for details.

5.5 Date and page ranges

These style redefines the \bibrangedash and \bibdatedash commands in order to get a simple hyphen (-) instead of an en dash (–) in the page and date ranges. If you prefer the en dash use the following code:

```
\DefineBibliographyExtras{<language>}{%
  \protected\def\bibrangedash{%
    \textendash\penalty\hyphenpenalty}%
  \protected\def\bibdatedash{\bibrangedash}}%
```

For a consistent result you probably have to do this for all the languages loaded by babel or polyglossia.

6 Backward compatibility

This section explain a different mechanism (now deprecated) to manage entries comprising both the original publication data and the translation data. This mechanism uses some special fields.

6.1 Deprecated fields

The following fields can hold the translation or the original edition data. They are precede by the string “trans.” or “orig. ed.”, respectively according to the origfields=trans (default) or origfields=origed option (see below). Note that the origdate/transdate field is needed in order to print these fields. Contrarily they will be ignored.

origtitle field (literal)

transtitle field (literal biber only)

The title of the translation/original edition.

origpublisher field (list)

transpublisher field (list biber only)

The publisher of the translation/original edition.

origlocation field (list)

translocation field (list biber only)

The location of the translation/original edition.

origdate field (range)

transdate field (range biber only)

The publication date of the translation/original edition.

Robert Bringhurst (1992), *The Elements of Typographic Style*, Hartley & Marks Publisher Inc., Vancouver, Canada; trad. it. *Gli elementi dello stile tipografico*, Sylvestre Bonnard, Milano 2009.

usera field (literal)

origbooktitle field (literal biber only)

transbooktitle field (literal biber only)

The title of the @collection/@book/@mvbook in which the translation/original edition of an @article (@inbook or @incollection) is published.

The field is printed after the origtitle/transtitle and the format is the same of the entry:

Moore, George Edward (1903), «The refutation of idealism», *Mind*, N.S., 12 (mag. 1903), p. 433-453; trad. it. «La confutazione dell'idealismo», in *Il Neoempirismo*, a cura di Alberto Pasquinelli, UTET, Torino 1969, p. 35-61.

userb field (literal)

orignote field (literal biber only)

transnote field (literal biber only)

This field is printed after the origtitle/transtitle. It is meant for secondary informations about the translation/original edition, such as the name of editors, translators, etc.:

Mach, E. (1883), *Die Mechanik in ihrer Entwicklung historisch-kritisch dargestellt*; trad. it. *La meccanica nel suo sviluppo storico-critico*, traduzione, introduzione e note di Alfonsina D'Elia, Bollati Boringhieri, Torino 1977.

userc field (literal)

origpages field (literal biber only)

transpages field (literal biber only)

This field is printed at the end of the entry, after the origdate/transdate field. It is meant for the page range of the translation/original edition or other useful informations. In the first case string “p.” is omitted.

6.2 Deprecated options

`origfields=trans, none, edorig` default: `trans`

- `true` Prints the `orig-` fields.
- `none` Omits the `orig-` fields.
- `origed` This option cites the translation data first and adds the original publication data at the end of the entry, preceded by the string “`orig. ed`” (or “`ed. orig.`” for Italian documents).

`origed=true, false` default: `true`

Same as the previous but can be set on a per-entry basis in the `options` field. (see Lobačevskij 1994).

`origfieldsformat=semicolon, parens, brackets` default: `semicolon`

- `semicolon` The translation/original publication data are preceded by a semicolon:

Poincaré, Jules-Henri (1968), *La science et l'hypothèse*, Paris, Flammarion; trad. it. *La scienza e l'ipotesi*, Milano, Bompiani 2003.

- `parens` Puts the translation or the original publication data in parentheses:

Poincaré, Jules-Henri (1968), *La science et l'hypothèse*, Paris, Flammarion (trad. it. *La scienza e l'ipotesi*, Milano, Bompiani 2003).

- `brackets` Same as the previous option but with brackets instead of parentheses:

Poincaré, Jules-Henri (1968), *La science et l'hypothèse*, Paris, Flammarion [trad. it. *La scienza e l'ipotesi*, Milano, Bompiani 2003].

References

The bibliography style of the document is `philosophy-modern`, but in this list of references we use `philosophy-classic` through the `restoreclassic` option. This is particularly useful for typesetting Web lists which.

Clawson, James (2010), *biblatex-mla*. *MLA Style Using biblatex*, version 0.95, <http://mirrors.ctan.org/macros/latex/contrib/biblatex-contrib/biblatex-mla/doc/biblatex-mla.pdf>.

The `biblatex-mla` files provide support to `biblatex`, `bibtex`, and `latex` for citations and Works Cited lists in the style established by the Modern Language Association (MLA).

Gliboff, Sander (2010), *User’s Guide to Historian. A Footnotes-and-Bibliography Style, Following Turabian/Chicago Guidelines: For Use with the Biblatex System of Programmable Bibliographies and Citations*, version 0.4, <http://mirrors.ctan.org/macros/latex/contrib/biblatex-contrib/biblatex-historian/historian.pdf>.

Historian follows the conventions of The Chicago Manual of Style, as presented in Turabian’s Manual for Writers.

Lehman, Philipp (2011), *The biblatex package. Programmable Bibliographies and Citations*, version 1.7, <http://mirrors.ctan.org/macros/latex/contrib/biblatex/doc/biblatex.pdf>.

This document is a systematic reference manual for the *biblatex* package. Look at the sample documents which ship with *biblatex* to get a first impression.

Pantieri, Lorenzo and Tommaso Gordini (2011), *L’arte di scrivere con L^AT_EX. Un’introduzione a L^AT_EX*, with a forew. by Enrico Gregorio, http://www.lorenzopantieri.net/LaTeX_files/ArteLaTeX.pdf.

The most popular Italian guide to L^AT_EX. A little masterpiece of style and typesetting.

Waßenhoven, Dominik (2011), *biblatex-dw*, version 1.4, <http://mirrors.ctan.org/macros/latex/contrib/biblatex-contrib/biblatex-dw/doc/biblatex-dw.pdf>.

A small collection of styles for the *biblatex* package. It was designed for citations in the Humanities and offers some features that are not provided by the standard *biblatex* styles.

Examples

Aristotle

- 1929 *Physics*, trans. by P. H. Wicksteed and F. M. Cornford, G. P. Putnam, New York.
A book entry with a `translator` field.

Corrocher, Roberto

- 2009 “Riflessioni sull’uomo di fronte a nuove sfide”, in Giarettta et al. (2009), pp. 27-42.
An `@incollection` entry. The `@collection` is automatically printed in the bibliography because another `@incollection` has been cited.

Federspil, Giovanni and Roberto Vettor

- 2009 “Medicina: un unico metodo e una sola argomentazione?”, in Giarettta et al. (2009), pp. 43-74.
An `@incollection` entry. The `@collection` is automatically printed in the bibliography because another `@incollection` has been cited.

Giarettta, Pierdaniele, Antonio Moretto, Gian Franco Gensini, and Marco Trabucchi

- 2009 (eds.), *Filosofia delle medicina. Metodo, modelli, cura ed errori*, 2 vols., il Mulino, Bologna.
A collection with four editors. The list is automatically truncated in the citations.

Guzmán de Rojas, Iván

- s.d. *Problemática lógico-lingüística de la comunicación social con el pueblo Aymara*, mimeo,
Con los auspicios del Centro internacional de Investigaciones para el Desarrollo de
Canada.
A work without a publication date. The string `nodate` (localized) is automatically printed.

Heidegger, Martin

- 2001 *Sein und Zeit*, 18th ed., Max Niemeyer Verlag, Tübingen. Apparso originariamente nel 1927 nell'annuario diretto da H. Husserl *Jahrbuch für Philosophie und phänomenologische Forschung* (vol. VIII).

Note the `library` field, use for some details about the first edition.

Kant, Immanuel

- 1968a *Kants Werke. Akademie Textausgabe*, Berlin.
- 1968b *Kritik der praktischen Vernunft*, in *Kants Werke. Akademie Textausgabe*, vol. 5: *Kritik der praktischen Vernunft. Kritik der Urtheilskraft*, Walter de Gruyter, Berlin, pp. 1-163.
An edition of Kant's *Collected Works*, volume five. This is an `inbook` entry which explicitly refers to the *Critique of Practical Reason* only, not to the entire fifth volume. Note the `author` and `bookauthor` fields in the database file. By default, the `bookauthor` is omitted if the values of the `author` and `bookauthor` fields are identical.
- 1968c *Kritik der praktischen Vernunft*, in Kant (1968a), vol. 5, pp. 1-163.
- 1968d *Kritik der Urtheilskraft*, in Kant (1968a), vol. 5, pp. 165-485.

Komensky, Jan Amos [Comenio]

- 1969 *Opera Omnia*, Praga.

This author is known with his Latin name, given in the `nameaddon` field.

Lobačevskij, Nikolaj Ivanovič

- 1994 *Nuovi principi della geometria. Con una teoria completa delle parallele*, ed. by Lucio Lombardo Radice, with a forew. by Evandro Agazzi, Bollati Boringhieri, Torino; orig. ed. 1835.
An entry typeset using the deprecated `orig-` fields mechanism.

Pantieri, Lorenzo and Tommaso Gordini

- 2011 *L'arte di scrivere con L^AT_EX. Un'introduzione a L^AT_EX*, with a forew. by Enrico Gregorio, http://www.lorenzopantieri.net/LaTeX_files/ArteLaTeX.pdf.
The most popular Italian guide to L^AT_EX. A little masterpiece of style and typesetting.

Poincaré, Jules-Henri

- 1968 *La science et l'hypothèse*, Flammarion, Paris; trans. *La scienza e l'ipotesi*, ed. by Corrado Sinigaglia, testo greco a fronte, Bompiani, Milano 2003.
A book entry followed by its translation, cross-referenced in the `related` field.

Popper, Karl R.

- 1934 *Logik der Forschung*, Springer, Wien; trad. ingl. *The Logic of Scientific Discovery*, 3rd ed., Hutchinson, London 1959; trans. *Logica della scoperta scientifica*, 3rd ed., Einaudi, Torino 1998.
A book entry followed by two different translations, cross-referenced in the `related` (biber 1.6 required).

Rossitto, Cristina

- 1977 “Opposizione e non contraddizione nella *Metafisica* di Aristotele”, in *La contraddizione*, ed. by Enrico Berti, Città Nuova, Roma, pp. 43-69.
Note that the `@collection` data (inherited from the `crossref` field) are printed inside the `@incollection` entry because this is the the only `@incollection` cited from that `@collection`.

Termini, Settimo

- 2007 “Vita morte e miracoli di Alan Mathison Turing”, in *Vite matematiche. Protagonisti del '900 da Hilbert a Wiles*, ed. by Claudio Bartocci, Renato Betti, Angelo Guerraggio, and Roberto Lucchetti, Springer-Verlag Italia, Milano.

Valbusa, Ivan

- 2007 “Psicologia e sistema in Alsted e in Wolff”, in *Christian Wolff tra psicologia empirica e psicologia razionale*, ed. by Ferdinando Luigi Marcolungo, Georg Olms Verlag, Hildesheim, Zürich, and London.

Web List

Here we have a list of Web sites typeset with the `philosophy-classic` style through the `restoresclassic` option.

CTAN (2006), *CTAN. The Comprehensive TeX Archive Network*, <http://www.ctan.org> (visited on 10/01/2006).

Note the `urldate` field and the `label` field, used for the citations.

GUIT. *Gruppo degli Utilizzatori Italiani di TeX* (2012), <http://www.guitex.org> (visited on 01/15/2012).

A Web site.

7 The Code

7.1 philosophy-standard.bbx

```
1 \RequireBiber[2]
2 \RequireBibliographyStyle{standard}
```

Load the localization modules:

```
3 \DeclareLanguageMapping{italian}{italian-philosophy}
4 \DeclareLanguageMapping{english}{english-philosophy}
5 \DeclareLanguageMapping{spanish}{spanish-philosophy}
```

7.1.1 Global options

```
6 \newtoggle{bbx:annotation}
7 \newtoggle{bbx:library}
8 \newtoggle{bbx:scauthors}
9 \newtoggle{bbx:scauthorsbib}
10 \newtoggle{bbx:inbeforejournal}
11 \newtoggle{bbx:classical}
12 \newtoggle{bbx:lowscauthors}
13
14 \newtoggle{cbx:shorthandintro}
15
16 \DeclareBibliographyOption{annotation}[true]{%
17   \settoggle{bbx:annotation}{#1}}
18 \DeclareBibliographyOption{library}[true]{%
19   \settoggle{bbx:library}{#1}}
20 \DeclareBibliographyOption{scauthors}[true]{%
```

```
21 \settoggle{bbx:scauthors}{#1}
22 \DeclareBibliographyOption{scauthorsbib}[true]{%
23   \settoggle{bbx:scauthorsbib}{#1}}
24 \DeclareBibliographyOption{inbeforejournal}[true]{%
25   \settoggle{bbx:inbeforejournal}{#1}}
26 \DeclareBibliographyOption{classical}[true]{%
27   \settoggle{bbx:classical}{#1}}
28 \DeclareBibliographyOption{lowscauthors}[true]{%
29   \settoggle{bbx:lowscauthors}{#1}}
30
31 \DeclareBibliographyOption{shorthandintro}[true]{%
32   \settoggle{cbx:shorthandintro}{#1}}
33
34
35 \newcommand{\bbx@publocformat}{}
36 \newcommand{\bbx@volnumformat}{}
37 \newcommand{\bbx@relatedformat}{}
38 \newcommand{\bbx@origfields}{}
39 \newcommand{\bbx@editionformat}{}
40 \newcommand{\bbx@volumeformat}{}
41
42 \DeclareBibliographyOption{publocformat}[publocyear]{%
43   \renewcommand{\bbx@publocformat}{#1}}
44 \DeclareBibliographyOption{volnumformat}[plain]{%
45   \renewcommand{\bbx@volnumformat}{#1}}
46 \DeclareBibliographyOption{origfieldsformat}[semicolon]{%
47   \renewcommand{\bbx@relatedformat}{#1}}
48 \DeclareBibliographyOption{relatedformat}[semicolon]{%
49   \renewcommand{\bbx@relatedformat}{#1}}
50 \DeclareBibliographyOption{origfields}[true]{%
51   \renewcommand{\bbx@origfields}{#1}}
52 \DeclareBibliographyOption{editionformat}[arabic]{%
53   \renewcommand{\bbx@editionformat}{#1}}
54 \DeclareBibliographyOption{volumeformat}[arabic]{%
55   \renewcommand{\bbx@volumeformat}{#1}}
56
57 \DeclareEntryOption{origed}[true]{%
58   \renewcommand{\bbx@origfields}{origed}}
59
60 \ExecuteBibliographyOptions{%
61   lowscauthors      = false,
62   publocformat     = publocyear,
63   annotation       = false,
64   library          = true,
65   scauthors        = false,
66   scauthorsbib    = false,
67   origfieldsformat = semicolon,
68   inbeforejournal  = false,
69   volnumformat     = plain,
70   editionformat    = arabic,
71   volumeformat     = arabic,
72   classical        = false,
```

```

73  useprefix      = true,
74  maxcitenames   = 2,
75  mincitenames   = 1,
76  maxbibnames    = 999,
77  minbibnames    = 999,
78  shorthandintro = true}

```

Changing the penalty of the urls will prevent many overfull boxes.

```

79 \setcounter{biburlnumpenalty}{9000}
80 \setcounter{biburlucpenalty}{9000}
81 \setcounter{biburllcpenalty}{9000}

```

These counters control the list of names of cross-referenced entries:

```

82 \newcounter{maxnamesincross}
83 \newcounter{minnamesincross}

```

7.1.2 Name format

```

84 \AtBeginDocument{%
85 \iftoggle{bbx:lowscauthors}{%
86   {\newrobustcmd*{\mkbibsc}[1]{\textsc{\MakeLowercase{\#1}}}}%
87   {\newrobustcmd*{\mkbibsc}[1]{\textsc{\#1}}}}%
88 \iftoggle{bbx:scauthors}{%
89   \toggletrue{bbx:scauthorsbib}%
90   \toggletrue{cbx:scauthorscite}}%
91 {}}
92 \AtBeginBibliography{%
93 \iftoggle{bbx:scauthorsbib}{%
94 \DeclareNameFormat{sortname}{%
95   \let\mkbibnamelast\mkbibsc%
96   \let\mkbibnamefirst\mkbibsc%
97   \let\mkbibnameprefix\mkbibsc%
98   \let\mkbibnameaffix\mkbibsc%
99   \ifnumequal{\value{listcount}}{1}%
100     {\iffirstinits
101       {\usebibmacro{name:last-first}{\#1}{\#4}{\#5}{\#7}}%
102       {\usebibmacro{name:last-first}{\#1}{\#3}{\#5}{\#7}}%
103     \ifblank{\#3\#5}
104       {}
105       {\usebibmacro{name:revsdelim}}}%
106     {\iffirstinits
107       {\usebibmacro{name:first-last}{\#1}{\#4}{\#5}{\#7}}%
108       {\usebibmacro{name:first-last}{\#1}{\#3}{\#5}{\#7}}}}%
109   \usebibmacro{name:andothers}}%
110 {}}%

```

7.1.3 New internal commands

```

111 \renewcommand*{\newunitpunct}{\addcomma\space}
112 \renewcommand*{\subtitlepunct}{\addperiod\space}
113 \renewcommand*{\intitlepunct}{\nopunct\addspace}
114 \newcommand*{\volnumpunct}{\addcomma\space}

```

We have to define a new internal command in order to get pure parenthesis for some specific fields when using the square option:

```

115 \newrobustcmd*{\mkpureparens}[1]{%
116   \begingroup
117   \blx@blxinit
118   \blx@setsfcodes
119   \blx@postpunct(#1\blx@postpunct)\midsentence%
120   \endgroup}

```

Indexing

```

121 \renewbibmacro*{citeindex}{%
122   \ifciteindex{\indexnames{labelname}}{}{%
123     \renewbibmacro*{bibindex}{%
124       \ifbibindex{\indexnames{author}}{%
125         \indexnames{editor}}{%
126         \indexnames{editora}}{%
127         \indexnames{editorb}}{%
128         \indexnames{editorc}}{%
129       }{}}{%

```

Font selection

```

130 \newcommand*{\annotationfont}{\footnotesize}
131 \newcommand*{\libraryfont}{}{%
132 \newcommand*{\editionfont}{%
133   \ifdefstring{\bbx@editionformat}{Roman}{%
134     {\uppercase}{%
135     \ifdefstring{\bbx@editionformat}{romansc}{%
136       {\scshape}{%
137       {\relax}{}}{%
138     }}}{%
139 \newrobustcmd*{\edfnt}[1]{%
140   \begingroup
141   \expandafter\editionfont
142   \expandafter{\romannumeral#1}{%
143   \endgroup}

```

7.1.4 Fields formats

```

144 \DeclareFieldFormat*[bookinbook,thesis]{title}{\mkbibemph{#1}}
145 \DeclareFieldFormat*[review]{title}{\bibstring{reviewof}\addspace#1}
146 \DeclareFieldFormat*[review]{citetitle}{\bibstring{reviewof}\addspace#1}
147 \DeclareFieldFormat*[inreference,article]{title}{\mkbibquote{#1}}
148 \DeclareFieldFormat*[bookinbook,thesis]{citetitle}{\mkbibemph{#1}}
149 \DeclareFieldFormat*[origtitle]{\mkbibemph{#1}}
150 \DeclareFieldFormat*[article]{origtitle}{\mkbibquote{#1}}
151 \DeclareFieldFormat*[usera]{\mkbibemph{#1}}
152 \DeclareFieldFormat*[bookinbook,inbook]{usera}{\mkbibemph{#1}}
153 \DeclareFieldFormat*[incollection]{usera}{\mkbibquote{#1}}
154 \DeclareFieldFormat*[userc]{\mkpageprefix[bookpagination]{#1}}
155 \DeclareFieldFormat*[url]{\url{#1}}
156 \DeclareFieldFormat*[annotation]{\annotationfont #1}
157 \DeclareFieldFormat*[library]{\libraryfont #1}
158 \DeclareFieldFormat*[backrefparens]{\mkpureparens{#1}}
159 \DeclareFieldFormat*[pureparens]{\mkpureparens{#1}}

```

```
160
161 \def\optionerror#1{%
162 \ClassError{biblatex-philosophy}{%
163   {\MessageBreak**** Unknown value for '#1' option}%
164   {\MessageBreak**** Unknown value for '#1' option}%
165 }
166
167 \DeclareFieldFormat{volume}{%
168   \bibstring{volume}%
169   \ifinteger{#1}{%
170     \ifdefstring{\bbx@volumeformat}{arabic}{%
171       {#1}%
172       \ifdefstring{\bbx@volumeformat}{Roman}{%
173         {\RN{#1}}%
174         \ifdefstring{\bbx@volumeformat}{romansc}{%
175           {\textsc{\Rn{#1}}}%
176           \ifdefstring{\bbx@volumeformat}{roman}{%
177             {\Rn{#1}}{\optionerror{volumeformat}}}}}}}}{#1}%
178
179 \DeclareFieldFormat[article]{volume}{%
180   \ifdefstring{\bbx@volnumformat}{strings}{%
181     {\bibstring{volume}}%
182     {}%
183     \ifinteger{#1}{%
184       \ifdefstring{\bbx@volumeformat}{arabic}{%
185         {#1}%
186         \ifdefstring{\bbx@volumeformat}{Roman}{%
187           {\RN{#1}}%
188           \ifdefstring{\bbx@volumeformat}{romansc}{%
189             {\textsc{\Rn{#1}}}%
190             \ifdefstring{\bbx@volumeformat}{roman}{%
191               {\Rn{#1}}{\optionerror{volumeformat}}}}}}}}{#1}%
192
193 \DeclareFieldFormat*[number]{%
194   \ifdefstring{\bbx@volnumformat}{strings}{%
195     \bibstring{number}~#1{#1}%
196   \DeclareFieldFormat*[series]{%
197     \ifinteger{#1}{%
198       {\mkbibordseries{#1}~\bibstring{jourser}}%
199       {\ifbibstring{#1}{\bibstring{#1}}{#1}}%
200   \DeclareFieldFormat{edition}{%
201     \ifinteger{#1}{%
202       \ifdefstring{\bbx@editionformat}{arabic}{%
203         {\mkbiborededition{#1}~\bibstring{edition}}%
204         \ifdefstring{\bbx@editionformat}{Roman}{%
205           {\RN{#1}~\bibstring{edition}}%
206           \ifdefstring{\bbx@editionformat}{romansc}{%
207             {\textsc{\Rn{#1}}~\bibstring{edition}}%
208             \ifdefstring{\bbx@editionformat}{roman}{%
209               {\Rn{#1}~\bibstring{edition}}%
210               {\optionerror{editionformat}}}}}}}}{#1}%
211   {#1}}% \isdot??
```

```

212 \DeclareFieldFormat{related}{%
213   \ifdefstring{\bbx@relatedformat}{parens}{%
214     {\mkpureparens{\#1}}%
215   }{\ifdefstring{\bbx@relatedformat}{brackets}{%
216     {\mkbibbrackets{\#1}}%
217   }{\ifdefstring{\bbx@relatedformat}{semicolon}{%
218     {\#1}{\optionerror{relatedformat}}}}}}%

```

7.1.5 The orig- macros (deprecated)

These macros are provided for backward compatibility. The new related field mechanism now directly support also this feature.

```

219 \newbibmacro*[origpublisher+origlocation+origdate]{%
220   \ifdefstring{\bbx@publocformat}{loccolonpub}{%
221     {\usebibmacro{origloccolonpub}\setunit{\bibpagespunct}}%
222       \printfield{userc}{\ifdefstring{\bbx@publocformat}{locpubyear}{%
223         {\usebibmacro{origlocpubyear}\setunit{\bibpagespunct}}%
224           \printfield{userc}{%
225             {\usebibmacro{origpublocyear}\setunit{\bibpagespunct}}%
226               \printfield{userc}}}}}}%
227 
228 \newbibmacro*[origpublocyear]{%
229   \iflistundef{origpublisher}{%
230     {\printlist{origlocation}{%
231       \setunit*{\addspace}%
232         \printorigdate}{%
233       {\printlist{origpublisher}{%
234         \setunit*{\addcomma\space}{%
235           \printlist{origlocation}{%
236             \setunit*{\addspace}{%
237               \printorigdate}{%
238                 \newunit}}}}}}}}%
239 
240 \newbibmacro*[origloccolonpub]{%
241   \iflistundef{origlocation}{%
242     {\printlist{origlocation}{%
243       \iflistundef{origpublisher}{%
244         {\setunit*{\addspace}{%
245           \printorigdate}{%
246             {\setunit*{\addcolon\space}{%
247               \printlist{origpublisher}{%
248                 \setunit*{\addcomma\space}{%
249                   \printorigdate}{%
250                     \newunit}}}}}}}}}}%
251 
252 \newbibmacro*[origlocpubyear]{%
253   \iflistundef{origlocation}{%
254     {\printlist{origlocation}{%
255       \iflistundef{origpublisher}{%
256         {\setunit*{\addspace}{%
257           \printorigdate}{%
258             {\setunit*{\addcomma\space}{%

```

```
259 \printlist{origpublisher}%
260 \setunit*{\addcomma\space}%
261 \printorigdate}%
262 \newunit}
263
264 \newbibmacro*[reprinttitle]{%
265   \iffieldundef{reprinttitle}{}{%
266     \iffieldsequal{reprinttitle}{title}{}{%
267       \printfield[title]{reprinttitle}%
268       \setunit{\addcomma\space}}}}%
269 \iffieldundef{userb}{}{%
270   \printfield{userb}}}%
271
272 \newbibmacro*[transorigstring]{%
273 \iffieldundef{reprinttitle}{}{%
274   {\printtext{\ifdefstring{\bbx@origfields}{origed}%
275   {\bibstring{origed}}}}%
276   {\bibstring{translationas}}}\nopunct}%
277 {\printtext{\bibstring{reprint}}}\nopunct}%
278
279 \newbibmacro*[origtitle:book]{%
280   \iffieldundef{origtitle}{}{%
281     \printfield[origtitle]{origtitle}%
282     \setunit{\addcomma\space}}}}%
283 \iffieldundef{userb}{}{%
284   \printfield{userb}}}%
285
286 \newbibmacro*[origtitledata:book]{%
287 \usebibmacro{transorigstring}%
288 \iffieldundef{reprinttitle}{}{%
289 {\usebibmacro{origtitle:book}}%
290 {\usebibmacro{reprinttitle}}}%
291 \newunit\newblock
292   \usebibmacro{origpublisher+origlocation+origdate}}%
293
294 \newbibmacro*[origdata:book]{%
295   \ifboolexpr{%
296     test {\iffieldundef{origtitle}}
297     and
298     test {\iffieldundef{origlocation}}
299     and
300     test {\iffieldundef{origpublisher}}
301     and
302     test {\iffieldundef{origyear}}
303   }%
304   {}%
305   {\ifdefstring{\bbx@relatedformat}{parens}%
306   {\nopunct\printtext[pureparens]{\usebibmacro{origtitledata:book}}}%
307   {\ifdefstring{\bbx@relatedformat}{brackets}%
308   {\nopunct\printtext[brackets]{\usebibmacro{origtitledata:book}}}%
309   {\setunit{\addsemicolon\space}}}}}}%
310   \printtext{\usebibmacro{origtitledata:book}}}}
```

```

311
312 \newbibmacro*{origtitle:article-inbook-incoll}{%
313   \iffieldundef{origtitle}{}{%
314     \printfield[origtitle]{origtitle}%
315   \setunit{\addcomma\space}%
316   \iffieldundef{usera}{}{%
317     \usebibmacro{in:}%
318     \printfield[usera]%
319       \setunit{\addcomma\space}%
320   \iffieldundef{userb}{}{%
321     \printfield[userb]%
322     \newunit}%
323
324 \newbibmacro*{origtitledata:article-inbook-incoll}{%
325   \usebibmacro{transorigstring}%
326   \setunit{\addspace}%
327   \usebibmacro{origtitle:article-inbook-incoll}%
328   \usebibmacro{origpublisher+origlocation+origdate}%
329
330 \newbibmacro*{origdata:article-inbook}{%
331   \iflistundef{origlocation}{}{%
332     \ifdefstring{\bbx@relatedformat}{parens}%
333       {\nopunct\printtext[pureparens]}{%
334         \usebibmacro{origtitledata:article-inbook-incoll}}%
335       \ifdefstring{\bbx@relatedformat}{brackets}%
336         {\nopunct\printtext[brackets]}{%
337           \usebibmacro{origtitledata:article-inbook-incoll}}%
338         \setunit{\addsemicolon\space}%
339       \printtext{%
340         \usebibmacro{origtitledata:article-inbook-incoll}}}}}}}

```

7.1.6 New macros

```

341 \renewbibmacro*{addendum+pubstate}{%
342   \printfield{addendum}%
343   \newunit\newblock
344   \printfield{pubstate}%
345   \ifdefstring{\bbx@origfields}{none}{}{%
346     \newunit\newblock
347     \usebibmacro{origdata:book}%
348     \newunit\newblock
349     \usebibmacro{library}%
350
351 \newbibmacro*{addendum+pubstate:article-inbook-incoll}{%
352   \printfield{addendum}%
353   \newunit\newblock
354   \printfield{pubstate}%
355   \ifdefstring{\bbx@origfields}{none}{}{%
356     \newunit\newblock
357     \usebibmacro{origdata:article-inbook}%
358     \newunit\newblock
359     \usebibmacro{library}}}

```

```
360
361 \newbibmacro*{volnumdefault}{%
362   \printfield{volume}%
363   \setunit*{\volumpunct}%
364   \printfield{number}}
365
366 \newbibmacro*{volnumparens}{%
367   \nopunct%
368   \printtext[pureparens]{%
369     \printfield{volume}%
370     \setunit*{\volumpunct}%
371     \printfield{number}}}
372
373 \newbibmacro*{volnumstrings}{%
374   \iffieldundef{volume}{}{%
375     \printfield{volume}\setunit*{\volumpunct}}%
376   \iffieldundef{number}{}{%
377     \printfield{number}}}
378
379 \renewbibmacro*{journal}{%
380   \iffieldundef{journaltitle}%
381   {}%
382   {\printtext[journaltitle]{%
383     \printfield[titlecase]{journaltitle}%
384     \midsentence%MOD#####
385     \setunit{\subtitlepunct}%
386     \printfield[titlecase]{journalsubtitle}}}}
387
388 \renewbibmacro*{periodical}{%
389   \iffieldundef{title}%
390   {}%
391   {\printtext[title]{%
392     \printfield[titlecase]{title}%
393     \midsentence%MOD#####
394     \setunit{\subtitlepunct}%
395     \printfield[titlecase]{subtitle}}}}
396
397 \renewbibmacro*{journal+issuetitle}{%
398   \usebibmacro{journal}%
399   \setunit*{\addspace}%
400   \iffieldundef{series}%
401   {}%
402   {\newunit%
403     \printfield{series}\setunit{\addspace}\midsentence}%
404     \newunit%
405   \usebibmacro{volume+number+eid}%
406   \setunit{\addspace}%
407   \usebibmacro{issue+date}%
408   \setunit{\addcolon\space}%
409   \usebibmacro{issue}%
410   \newunit}
411
```

```
412 \renewbibmacro*{title+issuetitle}{%
413   \usebibmacro{periodical}%
414   \setunit*{\addspace}%
415   \iffieldundef{series}%
416   {}
417   {\newunit
418     \printfield{series}%
419     \setunit{\addspace}\midsentence}%
420 \newunit
421 \usebibmacro{volume+number+eid}%
422 \setunit{\addcomma\space}%
423 \printfield{eid}%
424 \setunit{\addspace}%
425 \usebibmacro{issue+date}%
426 \setunit{\addcolon\space}%
427 \usebibmacro{issue}%
428 \newunit
429
430 \renewbibmacro*{volume+number+eid}{%
431   \ifdefstring{\bbx@volnumformat}{strings}%
432   { \usebibmacro{volnumstrings}}%
433   { \ifdefstring{\bbx@volnumformat}{parens}%
434   { \usebibmacro{volnumparens}}%
435   { \ifdefstring{\bbx@volnumformat}{plain}%
436   { \usebibmacro{volnumdefault}}%
437   { \optionerror{volnumformat}}}}%
438 \setunit{\addcomma\space}%
439 \printfield{eid}}
440
441 \renewbibmacro*{issue+date}{%
442   \printtext[pureparens]{%
443     \iffieldundef{issue}%
444     { \usebibmacro{date}}%
445     { \printfield{issue}%
446       \setunit*{\addspace}%
447       \usebibmacro{date}}}}%
448 \newunit
449
450 \renewbibmacro*{event+venue+date}{%v0.8
451   \printfield{eventtitle}%
452   \ifboolexpr{%
453     test {\iffieldundef{venue}}
454     and
455     test {\iffieldundef{eventyear}}}
456   }%
457   {}
458   {\setunit*{\addspace}%
459   \printtext{%
460     \printfield{venue}%
461     \setunit*{\addcomma\space}%
462     \printeventdate}}%
463 \newunit
```

```

464
465 \renewbibmacro*{series+number}{%
466   \printfield{series}%
467   \setunit{\addcomma\space}%
468   \printfield{number}%
469   \newunit}
470
471 \renewbibmacro*{publisher+location+date}{%
472 \ifdefstring{\bbx@publocformat}{loccolonpub}
473   {\usebibmacro{loccolonpub}}
474   {\ifdefstring{\bbx@publocformat}{locpubyear}
475     {\usebibmacro{locpubyear}}
476     {\ifdefstring{\bbx@publocformat}{publocyear}%
477       {\usebibmacro{publocyear}}{\optionerror{publocformat}}}}}
478
479 \renewbibmacro*{institution+location+date}{%
480 \ifdefstring{\bbx@publocformat}{loccolonpub}
481   {\usebibmacro{inloccolonpub}}
482   {\ifdefstring{\bbx@publocformat}{locpubyear}
483     {\usebibmacro{inlocpubyear}}
484     {\ifdefstring{\bbx@publocformat}{publocyear}%
485       {\usebibmacro{inpublocyear}}{\optionerror{publocformat}}}}}
486
487 \renewbibmacro*{organization+location+date}{%
488 \ifdefstring{\bbx@publocformat}{loccolonpub}
489   {\usebibmacro{orgloccolonpub}}
490   {\ifdefstring{\bbx@publocformat}{locpubyear}
491     {\usebibmacro{orglocpubyear}}
492     {\ifdefstring{\bbx@publocformat}{publocyear}%
493       {\usebibmacro{orgpublocyear}}{\optionerror{publocformat}}}}}
494
495 \newbibmacro*{library}{%
496 \iftoggle{bbx:library}{%
497   \iffieldundef{library}%
498   {}%
499   {\setunit{\addperiod\space}%
500     {\printfield{library}}}}%
501   {}}

```

In this macro the `\nopunct` command is needed to avoid the dot after the parentheses.

```

502 \renewbibmacro*{pageref}{%
503   \iflistundef{pageref}
504   {}%
505   {\setunit{\addperiod\space}%
506     \printtext[backrefparens]{%
507       \ifnumgreater{\value{pageref}}{1}
508         {\bibstring[backrefpages]\ppspace}%
509       {\bibstring[backrefpage]\ppspace}%
510       \printlist[pageref]{-\value{listtotal}}{\pageref}\adddot\nopunct}}}
511
512 \renewbibmacro*{finentry}{%
513   \iftoggle{bbx:annotation}{%

```

```
514 {\iffieldundef{annotation}%
515   {\finentry}%
516   {\setunit{\addperiod\par\nobreak\vspace*{.5ex}}%
517    \printtext[annotation]{\printfield{annotation}\finentry\par}}}}%
518 {\finentry}%
519
520 \newbibmacro*[publocyear]{%
521   \iflistundef{publisher}%
522   {}%
523   {\printlist[publisher]}%
524   \setunit*{\addcomma\space}%
525   \printlist[location]%
526   \usebibmacro{relateddate}%
527 \newunit}%
528
529 \newbibmacro*[inpublocyear]{%
530   \iflistundef{institution}%
531   {}%
532   {\printlist[institution]}%
533   \setunit*{\addcomma\space}%
534   \printlist[location]%
535   \usebibmacro{relateddate}%
536 \newunit}%
537
538 \newbibmacro*[orgpublocyear]{%
539   \iflistundef{organization}%
540   {}%
541   {\printlist[organization]}%
542   \setunit*{\addcomma\space}%
543   \printlist[location]%
544   \usebibmacro{relateddate}%
545 \newunit}%
546
547 \newbibmacro*[loccolonpub]{%
548   \printlist[location]%
549   \iflistundef{publisher}%
550   {\setunit*{\addspace}%
551   {\setunit*{\addcolon\space}}}%
552   \printlist[publisher]}%
553   \usebibmacro{commarelateddate}%
554 \newunit}%
555
556 \newbibmacro*[inloccolonpub]{%
557   \printlist[location]%
558   \iflistundef{institution}%
559   {\setunit*{\addspace}%
560   {\setunit*{\addcolon\space}}}%
561   \printlist[institution]}%
562   \usebibmacro{commarelateddate}%
563   \newunit}%
564
565 \newbibmacro*[orgloccolonpub]{%
```

```

566 \printlist{location}%
567 \iflistundef{organization}%
568   {\setunit*{\addspace}%
569   {\setunit*{\addcolon\space}}%}
570 \printlist{organization}%
571 \usebibmacro{commarelateddate}%
572 \newunit}
573
574 \newbibmacro*{loccpubyear}{%
575   \printlist{location}%
576 \iflistundef{publisher}%
577   {\setunit*{\addspace}%
578   {\setunit*{\addcomma\space}}%}
579 \printlist{publisher}%
580 \usebibmacro{commarelateddate}%
581 \newunit}
582
583 \newbibmacro*{inloccpubyear}{%
584   \printlist{location}%
585 \iflistundef{institution}%
586   {\setunit*{\addspace}%
587   {\setunit*{\addcomma\space}}%}
588 \printlist{institution}%
589 \usebibmacro{commarelateddate}%
590 \newunit}
591
592 \newbibmacro*{orgloccpubyear}{%
593   \printlist{location}%
594 \iflistundef{organization}%
595   {\setunit*{\addspace}%
596   {\setunit*{\addcomma\space}}%}
597 \printlist{organization}%
598 \usebibmacro{commarelateddate}%
599 \newunit}

```

7.1.7 The related field mechanism

```

600 \newbibmacro*{relateddate}{%
601   \setunit*{\addspace}%
602   \printdate}
603 \newbibmacro*{commarelateddate}{%
604   \setunit*{\addcomma\space}%
605   \printdate}

```

A trick to delete the author/editor list for related entries and \ccite command:

```

606 \newbibmacro*{related:clearauthors}{%
607   \renewbibmacro*{author/translator+others}{\usebibmacro{bbx:savehash}}%
608   \renewbibmacro*{author/editor+others/translator+others}{\usebibmacro{bbx:savehash}}%
609   \renewbibmacro*{editor+others}{\usebibmacro{bbx:savehash}}%
610   \renewbibmacro*{author/translator+others}{\usebibmacro{bbx:savehash}}%
611   \renewbibmacro*{author/editor}{\usebibmacro{bbx:savehash}}%
612   \renewbibmacro*{author}{\usebibmacro{bbx:savehash}}%
613   \renewbibmacro*{editor}{\usebibmacro{bbx:savehash}}%
614   \renewcommand*{\labelnamepunct}{}}%

```

```

615
616 \DeclareCiteCommand{\relatedcite}
617   {}%
618   {\usedriver
619     {\DeclareNameAlias{sortname}{default}%
620      \usebibmacro{related:clearauthors}%
621      \renewbibmacro*{relateddate}%
622        {\setunit{\addspace}\printdate}%
623      \renewbibmacro*{comparerelateddate}%
624        {\setunit{\addcomma\space}\printdate}%
625        {\thefield{entrytype}}}%
626   {}%
627   {}%
628
629 \renewbibmacro*{related:default}[1]{%
630   \togglefalse{cbx:scauthorscite}%
631   \togglefalse{bbx:annotation}%
632 \iffieldundef{relatedstring}%
633   {\bibstring{translationas}\space}%
634   {\setunit{\bibstring{translationas}\space}}%
635   \renewcommand*{\mkpureparens}{\unspace\addsemicolon\space}%horrible trick
636   \renewcommand*{\mkbibbrackets}{\unspace\addsemicolon\space}%horrible trick
637   \relatedcite{\thefield{related}}}

```

7.1.8 Bibliography drivers

```

638 \DeclareBibliographyDriver{article}{%
639   \usebibmacro{bibindex}%
640   \usebibmacro{begentry}%
641   \usebibmacro{author/translator+others}%
642   \setunit{\labelnamepunct}\newblock
643   \usebibmacro{title}%
644   \newunit
645   \printlist[language]%
646   \newunit\newblock
647   \usebibmacro{byauthor}%
648   \newunit\newblock
649   \usebibmacro{bytranslator+others}%
650   \newunit\newblock
651   \printfield{version}%
652   \newunit\newblock
653   \iftoggle{bbx:inbeforejournal}{\usebibmacro{in:}}{}%
654   \usebibmacro{journal+issuetitle}%
655   \newunit\newblock
656   \usebibmacro{byeditor+others}%
657   \newunit\newblock
658   \usebibmacro{note+pages}%
659   \newunit\newblock
660   \iftoggle{bbx:isbn}
661     {\printfield{issn}}
662     {}%
663   \newunit\newblock
664   \usebibmacro{doi+eprint+url}%

```

```
665 \newunit\newblock
666 \usebibmacro{addendum+pubstate:article-inbook-incoll}%
667 \newblock
668 \iftoggle{bbx:related}
669   {\ifdefstring{\bbx@relatedformat}{semicolon}{\setunit{\addsemicolon\space}}%
670   {\setunit{\unspace\space}}%horrible trick
671   \usebibmacro{related:init}%
672   \usebibmacro{related}%
673   {}%
674 \newunit\newblock
675 \usebibmacro{pageref}%
676 \usebibmacro{finentry}%
677
678 \DeclareBibliographyDriver{book}{%
679   \usebibmacro{bibindex}%
680   \usebibmacro{begentry}%
681   \usebibmacro{author/editor+others/translator+others}%
682   \setunit{\labelnamepunct}\newblock
683   \usebibmacro{maintitle+title}%
684 \newunit
685   \printlist{language}%
686 \newunit\newblock
687   \usebibmacro{byauthor}%
688 \newunit\newblock
689   \usebibmacro{byeditor+others}%
690 \newunit\newblock
691   \printfield{edition}%
692 \newunit
693   \printfield{volumes}%
694 \newunit\newblock
695   \usebibmacro{series+number}%
696 \newunit\newblock
697   \printfield{note}%
698 \newunit\newblock
699   \usebibmacro{publisher+location+date}%
700 \newunit
701 \iffieldundef{maintitle}
702   {\printfield{volume}%
703   \printfield{part}%
704   {}%
705 \newunit\newblock
706   \usebibmacro{chapter+pages}%
707 \newunit
708   \printfield{pagetotal}%
709 \newunit\newblock
710 \iftoggle{bbx:isbn}
711   {\printfield{isbn}%
712   {}%
713 \newunit\newblock
714   \usebibmacro{doi+eprint+url}%
715 \newunit\newblock
716   \usebibmacro{addendum+pubstate}%
717 }
```

```
717 \newblock
718 \iftoggle{bbx:related}
719   {\ifdefstring{\bbx@relatedformat}{semicolon}%
720    {\setunit{\addsemicolon\space}}%
721    {\setunit{\unspace\space}}%horrible trick
722    \usebibmacro{related:init}%
723    \usebibmacro{related}{}%
724  }%
725 \newunit\newblock
726 \usebibmacro{pageref}%
727 \usebibmacro{finentry}%
728
729 \DeclareBibliographyDriver{booklet}{%
730   \usebibmacro{bibindex}%
731   \usebibmacro{begentry}%
732   \usebibmacro{author/editor+others/translator+others}%
733   \setunit{\labelnamepunct}\newblock
734   \usebibmacro{title}%
735   \newunit
736   \printlist{language}%
737   \newunit\newblock
738   \usebibmacro{byauthor}%
739   \newunit\newblock
740   \usebibmacro{byeditor+others}%
741   \newunit\newblock
742   \printfield{howpublished}%
743   \newunit\newblock
744   \printfield{type}%
745   \newunit\newblock
746   \printfield{note}%
747   \newunit\newblock
748   \usebibmacro{location+date}%
749   \newunit\newblock
750   \usebibmacro{chapter+pages}%
751   \newunit
752   \printfield{pagetotal}%
753   \newunit\newblock
754   \usebibmacro{doi+eprint+url}%
755   \newunit\newblock
756   \usebibmacro{addendum+pubstate}%
757   \newblock
758 \iftoggle{bbx:related}
759   {\ifdefstring{\bbx@relatedformat}{semicolon}%
760    {\setunit{\addsemicolon\space}}%
761    {\setunit{\unspace\space}}%horrible trick
762    \usebibmacro{related:init}%
763    \usebibmacro{related}{}%
764  }%
765 \newunit\newblock
766 \usebibmacro{pageref}%
767 \usebibmacro{finentry}%
768
```

```
769 \DeclareBibliographyDriver{collection}{%
770   \usebibmacro{bibindex}%
771   \usebibmacro{begentry}%
772   \usebibmacro{editor+others}%
773   \setunit{\labelnamepunct}\newblock
774   \usebibmacro{maintitle+title}%
775   \newunit
776   \printlist{language}%
777   \newunit\newblock
778   \usebibmacro{byeditor+others}%
779   \newunit\newblock
780   \printfield{edition}%
781   \newunit
782   \iffieldundef{maintitle}%
783     {\printfield{volume}%
784      \printfield{part}%
785    {}%
786   \newunit
787   \printfield{volumes}%
788   \newunit\newblock
789   \usebibmacro{series+number}%
790   \newunit\newblock
791   \printfield{note}%
792   \newunit\newblock
793   \usebibmacro{publisher+location+date}%
794   \newunit\newblock
795   \usebibmacro{chapter+pages}%
796   \newunit
797   \printfield{pagetotal}%
798   \newunit\newblock
799   \iftoggle{bbx:isbn}%
800     {\printfield{isbn}%
801    {}%
802   \newunit\newblock
803   \usebibmacro{doi+eprint+url}%
804   \newunit\newblock
805   \usebibmacro{addendum+pubstate}%
806   \newblock
807   \iftoggle{bbx:related}%
808     {\ifdefstring{\bbx:relatedformat}{semicolon}%
809       {\setunit{\addsemicolon\space}}%
810       {\setunit{\unspace\space}}%horrible trick
811     \usebibmacro{related:init}%
812     \usebibmacro{related}{}%
813    {}%
814   \newunit\newblock
815   \usebibmacro{pageref}%
816   \usebibmacro{finentry}%
817
818 \DeclareBibliographyDriver{inbook}{%
819   \togglefalse{cbx:scauthorscite}%
820   \usebibmacro{bibindex}%
```

```
821 \usebibmacro{begentry}%
822 \usebibmacro{author/translator+others}%
823 \setunit{\labelnamepunct}\newblock
824 \usebibmacro{title}%
825 \newunit
826 \printlist{language}%
827 \newunit\newblock
828 \usebibmacro{byauthor}%
829 \newunit\newblock
830 \usebibmacro{in:}%
831 \iffieldundef{xref}%
832 {\iffieldundef{crossref}{\usebibmacro{inbook:full}}%
833 {\bbx@crossref@inbook{\thefield{crossref}}}%
834 \newunit\newblock
835 \usebibmacro{crossrefdata}{}%
836 {\bbx@crossref@inbook{\thefield{xref}}}%
837 \newunit\newblock
838 \usebibmacro{xrefdata}{}%
839
840 \newbibmacro*[inbook:full]{%
841 \usebibmacro{bybookauthor}%
842 \newunit\newblock
843 \usebibmacro{maintitle+booktitle}%
844 \newunit\newblock
845 \usebibmacro{byeditor+others}%
846 \newunit\newblock
847 \printfield{edition}%
848 \newunit
849 \printfield{volumes}%
850 \newunit\newblock
851 \usebibmacro{series+number}%
852 \newunit\newblock
853 \printfield{note}%
854 \newunit\newblock
855 \usebibmacro{publisher+location+date}%
856 \newunit
857 \iffieldundef{maintitle}%
858 {\printfield{volume}%
859 \printfield{part}%
860 {}%
861 \newunit\newblock
862 \usebibmacro{chapter+pages}%
863 \newunit\newblock
864 \iftoggle{bbx:isbn}%
865 {\printfield{isbn}%
866 {}%
867 \newunit\newblock
868 \usebibmacro{doi+eprint+url}%
869 \newunit\newblock
870 \usebibmacro{addendum+pubstate:article-inbook-incoll}%
871 \newblock
872 \iftoggle{bbx:related}
```

```
873  {\ifdefstring{\bbx@relatedformat}{semicolon}%
874  {\setunit{\addsemicolon\space}}%
875  {\setunit{\unspace\space}}%horrible trick
876  \usebibmacro{related:init}%
877  \usebibmacro{related}%%
878  {}%
879  \newunit\newblock
880  \usebibmacro{pageref}%
881  \usebibmacro{finentry}%
882
883 \DeclareBibliographyDriver{incollection}{%
884 \togglefalse{cbx:scauthorscite}%
885  \usebibmacro{bibindex}%
886  \usebibmacro{begentry}%
887  \usebibmacro{author/translator+others}%
888  \setunit{\labelnamepunct}\newblock
889  \usebibmacro{title}%
890  \newunit
891  \printlist{language}%
892  \newunit\newblock
893  \usebibmacro{byauthor}%
894  \newunit\newblock
895  \usebibmacro{in:}%
896  \iffieldundef{xref}%
897  {\iffieldundef{crossref}{\usebibmacro{incollection:full}}%
898  {\bbx@crossref@incollection{\thefield{crossref}}}}
899  \newunit\newblock
900  \usebibmacro{crossrefdata}%%
901  {\bbx@crossref@incollection{\thefield{xref}}}
902  \newunit\newblock
903  \usebibmacro{xrefdata}%%
904
905  \newbibmacro*[incollection:full]{%
906  \usebibmacro{maintitle+booktitle}%
907  \newunit\newblock
908  \usebibmacro{byeditor+others}%
909  \newunit\newblock
910  \printfield{edition}%
911  \newunit
912  \printfield{volumes}%
913  \newunit\newblock
914  \usebibmacro{series+number}%
915  \newunit\newblock
916  \printfield{note}%
917  \newunit\newblock
918  \usebibmacro{publisher+location+date}%
919  \newunit
920  \iffieldundef{maintitle}%
921  {\printfield{volume}%
922  \printfield{part}%
923  {}%
924  \newunit\newblock}
```

```
925 \usebibmacro{chapter+pages}%
926 \newunit\newblock
927 \iftoggle{bbx:isbn}
928   {\printfield{isbn}}
929   {}%
930 \newunit\newblock
931 \usebibmacro{doi+eprint+url}%
932 \newunit\newblock
933 \usebibmacro{addendum+pubstate:article-inbook-incoll}%
934 \newblock
935 \iftoggle{bbx:related}
936   {\ifdefstring{\bbx@relatedformat}{semicolon}%
937     {\setunit{\addsemicolon\space}}%
938     {\setunit{\unspace\space}}%horrible trick
939   \usebibmacro{related:init}%
940   \usebibmacro{related}%
941   {}%
942 \newunit\newblock
943 \usebibmacro{pageref}%
944 \usebibmacro{finentry}%
945
946 \DeclareBibliographyDriver{inproceedings}{%
947 \togglefalse{cbx:scauthorscite}%
948 \usebibmacro{bibindex}%
949 \usebibmacro{begentry}%
950 \usebibmacro{author/translator+others}%
951 \setunit{\labelnamepunct}\newblock
952 \usebibmacro{title}%
953 \newunit
954 \printlist[language]%
955 \newunit\newblock
956 \usebibmacro{byauthor}%
957 \newunit\newblock
958 \usebibmacro{in:}%
959 \iffieldundef{xref}%
960   {\iffieldundef{crossref}{\usebibmacro{inproceedings:full}}%
961   {\bbx@crossref@incollection{\thefield{crossref}}}}
962 \newunit\newblock
963 \usebibmacro{crossrefdata}%%
964 {\bbx@crossref@incollection{\thefield{xref}}}
965 \newunit\newblock
966 \usebibmacro{xrefdata}%%
967
968 \newbibmacro*{inproceedings:full}{%
969   \usebibmacro{maintitle+booktitle}%
970   \newunit\newblock
971   \usebibmacro{event+venue+date}%
972   \newunit\newblock
973   \usebibmacro{byeditor+others}%
974   \newunit
975   \printfield{volumes}%
976   \newunit\newblock
```

```
977 \usebibmacro{series+number}%
978 \newunit\newblock
979 \printfield{note}%
980 \newunit\newblock
981 \printlist{organization}%
982 \newunit
983 \usebibmacro{publisher+location+date}%
984 \newunit
985 \iftoggle{bbx:isbn}{%
986   \printfield{volume}%
987   \printfield{part}%
988 }%
989 \newunit\newblock
990 \usebibmacro{chapter+pages}%
991 \newunit\newblock
992 \iftoggle{bbx:isbn}{%
993   \printfield{isbn}%
994 }%
995 \newunit\newblock
996 \usebibmacro{doi+eprint+url}%
997 \newunit\newblock
998 \usebibmacro{addendum+pubstate:article-inbook-incoll}%
999 \newblock
1000 \iftoggle{bbx:related}{%
1001   {\ifdefstring{\bbx@relatedformat}{semicolon}{%
1002     \setunit{\addsemicolon\space}%
1003     \setunit{\unspace\space}}%horrible trick
1004   \usebibmacro{related:init}%
1005   \usebibmacro{related}%
1006 }%
1007 \newunit\newblock
1008 \usebibmacro{pageref}%
1009 \usebibmacro{finentry}%
1010
1011 \DeclareBibliographyDriver{manual}{%
1012   \usebibmacro{bibindex}%
1013   \usebibmacro{begentry}%
1014   \usebibmacro{author/editor}%
1015   \setunit{\labelnamepunct}\newblock
1016   \usebibmacro{title}%
1017   \newunit
1018   \printlist{language}%
1019   \newunit\newblock
1020   \usebibmacro{byauthor}%
1021   \newunit\newblock
1022   \usebibmacro{byeditor}%
1023   \newunit\newblock
1024   \printfield{edition}%
1025   \newunit\newblock
1026   \usebibmacro{series+number}%
1027   \newunit\newblock
1028   \printfield{type}%

```

```
1029 \newunit
1030 \printfield{version}%
1031 \newunit
1032 \printfield{note}%
1033 \newunit\newblock
1034 \printlist{organization}%
1035 \newunit
1036 \usebibmacro{publisher+location+date}%
1037 \newunit\newblock
1038 \usebibmacro{chapter+pages}%
1039 \newunit
1040 \printfield{pagetotal}%
1041 \newunit\newblock
1042 \iftoggle{bbx:isbn}
  {\printfield{isbn}}
  {}%
1043 \newunit\newblock
1044 \usebibmacro{doi+eprint+url}%
1045 \newunit\newblock
1046 \usebibmacro{addendum+pubstate}%
1047 \newblock
1048 \iftoggle{bbx:related}
  {\ifdefstring{\bbx@relatedformat}{semicolon}%
   {\setunit{\addsemicolon\space}}%
   {\setunit{\unspace\space}}%\horrible trick
    \usebibmacro{related:init}%
    \usebibmacro{related}{}%
  {}%
1049 \newunit\newblock
1050 \usebibmacro{pageref}%
1051 \usebibmacro{finentry}%
1052 \newunit
1053 \DeclareBibliographyDriver{misc}{%
1054   \usebibmacro{bibindex}%
1055   \usebibmacro{begentry}%
1056   \usebibmacro{author/editor+others/translator+others}%
1057   \setunit{\labelnamepunct}\newblock
1058   \usebibmacro{title}%
1059   \newunit
1060   \printlist{language}%
1061   \newunit\newblock
1062   \usebibmacro{byauthor}%
1063   \newunit\newblock
1064   \usebibmacro{byeditor+others}%
1065   \newunit\newblock
1066   \printfield{howpublished}%
1067   \newunit\newblock
1068   \printfield{type}%
1069   \newunit
1070   \printfield{version}%
1071   \newunit
1072   \printfield{note}%
1073 }
```

```
1081 \newunit\newblock
1082 \usebibmacro{organization+location+date}%
1083 \newunit\newblock
1084 \usebibmacro{doi+eprint+url}%
1085 \newunit\newblock
1086 \usebibmacro{addendum+pubstate}%
1087 \newblock
1088 \iftoggle{bbx:related}
1089   {\ifdefstring{\bbx@relatedformat}{semicolon}%
1090    {\setunit{\addsemicolon\space}}%
1091    {\setunit{\unspace\space}}%horrible trick
1092   \usebibmacro{related:init}%
1093     \usebibmacro{related}%
1094   {}%
1095 \newunit\newblock
1096 \usebibmacro{pageref}%
1097 \usebibmacro{finentry}%
1098
1099 \DeclareBibliographyDriver{online}{%
1100   \usebibmacro{bibindex}%
1101   \usebibmacro{begentry}%
1102   \usebibmacro{author/editor+others/translator+others}%
1103   \setunit{\labelnamepunct}\newblock
1104   \usebibmacro{title}%
1105   \newunit
1106   \printlist{language}%
1107   \newunit\newblock
1108   \usebibmacro{byauthor}%
1109   \newunit\newblock
1110   \usebibmacro{byeditor+others}%
1111   \newunit\newblock
1112   \printfield{version}%
1113   \newunit
1114   \printfield{note}%
1115   \newunit\newblock
1116   \printlist{organization}%
1117   \newunit\newblock
1118   \usebibmacro{date}%
1119   \newunit\newblock
1120   \iftoggle{bbx:eprint}
1121     {\usebibmacro{eprint}%
1122     {}%
1123   \newunit\newblock
1124   \usebibmacro{url+urldate}%
1125   \newunit\newblock
1126   \usebibmacro{addendum+pubstate}%
1127   \newblock
1128   \iftoggle{bbx:related}
1129     {\ifdefstring{\bbx@relatedformat}{semicolon}%
1130      {\setunit{\addsemicolon\space}}%
1131      {\setunit{\unspace\space}}%horrible trick
1132     \usebibmacro{related:init}%
1133 }
```

```
1133     \usebibmacro{related}%
1134     {}%
1135     \newunit\newblock
1136     \usebibmacro{pageref}%
1137     \usebibmacro{finentry}%
1138
1139 \DeclareBibliographyDriver{patent}{%
1140     \usebibmacro{bibindex}%
1141     \usebibmacro{begentry}%
1142     \usebibmacro{author}%
1143     \setunit{\labelnamepunct}\newblock
1144     \usebibmacro{title}%
1145     \newunit
1146     \printlist{language}%
1147     \newunit\newblock
1148     \usebibmacro{byauthor}%
1149     \newunit\newblock
1150     \printfield{type}%
1151     \setunit*{\addspace}%
1152     \printfield{number}%
1153     \iflistundef{location}%
1154     {}
1155     {\setunit*{\addspace}%
1156      \printtext[parens]{%
1157          \printlist[][-\value{listtotal}]{location}}}%
1158     \newunit\newblock
1159     \usebibmacro{byholder}%
1160     \newunit\newblock
1161     \printfield{note}%
1162     \newunit\newblock
1163     \usebibmacro{date}%
1164     \newunit\newblock
1165     \usebibmacro{doi+eprint+url}%
1166     \newunit\newblock
1167     \usebibmacro{addendum+pubstate}%
1168     \newblock
1169     \iftoggle{bbx:related}%
1170         {\ifdefstring{\bbx@relatedformat}{semicolon}%
1171          {\setunit{\addsemicolon\space}}%
1172          {\setunit{\unspace\space}}%horrible trick
1173          \usebibmacro{related:init}%
1174          \usebibmacro{related}%
1175         {}%
1176         \newunit\newblock
1177         \usebibmacro{pageref}%
1178         \usebibmacro{finentry}%
1179
1180 \DeclareBibliographyDriver{periodical}{%
1181     \usebibmacro{bibindex}%
1182     \usebibmacro{begentry}%
1183     \usebibmacro{editor}%
1184     \setunit{\labelnamepunct}\newblock
```

```
1185 \usebibmacro{title+issuetitle}%
1186 \newunit
1187 \printlist{language}%
1188 \newunit\newblock
1189 \usebibmacro{byeditor}%
1190 \newunit\newblock
1191 \printfield{note}%
1192 \newunit\newblock
1193 \iftoggle{bbx:isbn}
1194   {\printfield{issn}}
1195   {}%
1196 \newunit\newblock
1197 \usebibmacro{doi+eprint+url}%
1198 \newunit\newblock
1199 \usebibmacro{addendum+pubstate}%
1200 \newblock
1201 \iftoggle{bbx:related}
1202   {\ifdefstring{\bbx@relatedformat}{semicolon}%
1203    {\setunit{\addsemicolon\space}}%
1204    {\setunit{\unspace\space}}%horrible trick
1205   \usebibmacro{related:init}%
1206   \usebibmacro{related}%
1207   {}%
1208 \newunit\newblock
1209 \usebibmacro{pageref}%
1210 \usebibmacro{finentry}%
1211
1212 \DeclareBibliographyDriver{proceedings}{%
1213   \usebibmacro{bibindex}%
1214   \usebibmacro{begentry}%
1215   \usebibmacro{editor+others}%
1216   \setunit{\labelnamepunct}\newblock
1217   \usebibmacro{maintitle+title}%
1218   \newunit
1219   \printlist{language}%
1220   \newunit\newblock
1221   \usebibmacro{event+venue+date}%
1222   \newunit\newblock
1223   \usebibmacro{byeditor+others}%
1224   \newunit\newblock
1225   \iffieldundef{maintitle}
1226     {\printfield{volume}%
1227      \printfield{part}%
1228     {}%
1229   \newunit
1230   \printfield{volumes}%
1231   \newunit\newblock
1232   \usebibmacro{series+number}%
1233   \newunit\newblock
1234   \printfield{note}%
1235   \newunit\newblock
1236   \printlist{organization}%
1237 }
```

```
1237 \newunit
1238 \usebibmacro{publisher+location+date}%
1239 \newunit\newblock
1240 \usebibmacro{chapter+pages}%
1241 \newunit
1242 \printfield{pagetotal}%
1243 \newunit\newblock
1244 \iftoggle{bbx:isbn}
1245   {\printfield{isbn}}
1246   {}%
1247 \newunit\newblock
1248 \usebibmacro{doi+eprint+url}%
1249 \newunit\newblock
1250 \usebibmacro{addendum+pubstate}%
1251 \newblock
1252 \iftoggle{bbx:related}
1253   {\ifdefstring{\bbx@relatedformat}{semicolon}%
1254     {\setunit{\addsemicolon\space}}%
1255     {\setunit{\unspace\space}}%horrible trick
1256   \usebibmacro{related:init}%
1257   \usebibmacro{related}{}%
1258   {}%
1259 \newunit\newblock
1260 \usebibmacro{pageref}%
1261 \usebibmacro{finentry}%
1262
1263 \DeclareBibliographyDriver{report}%
1264   \usebibmacro{bibindex}%
1265   \usebibmacro{begentry}%
1266   \usebibmacro{author}%
1267   \setunit{\labelnamepunct}\newblock
1268   \usebibmacro{title}%
1269   \newunit
1270   \printlist{language}%
1271   \newunit\newblock
1272   \usebibmacro{byauthor}%
1273   \newunit\newblock
1274   \printfield{type}%
1275   \setunit*{\addspace}%
1276   \printfield{number}%
1277   \newunit\newblock
1278   \printfield{version}%
1279   \newunit
1280   \printfield{note}%
1281   \newunit\newblock
1282   \usebibmacro{institution+location+date}%
1283   \newunit\newblock
1284   \usebibmacro{chapter+pages}%
1285   \newunit
1286   \printfield{pagetotal}%
1287   \newunit\newblock
1288 \iftoggle{bbx:isbn}
```

```
1289     {\printfield{isrn}}%
1290     {}%
1291 \newunit\newblock
1292 \usebibmacro{doi+eprint+url}%
1293 \newunit\newblock
1294 \usebibmacro{addendum+pubstate}%
1295 \newblock
1296 \iftoggle{bbx:related}%
1297   {\ifdefstring{\bbx@relatedformat}{semicolon}%
1298    {\setunit{\addsemicolon\space}}%
1299    {\setunit{\unspace\space}}%horrible trick
1300   \usebibmacro{related:init}%
1301   \usebibmacro{related}%
1302   {}%
1303 \newunit\newblock
1304 \usebibmacro{pageref}%
1305 \usebibmacro{finentry}%
1306
1307 \DeclareBibliographyDriver{thesis}%
1308   \usebibmacro{bibindex}%
1309   \usebibmacro{begentry}%
1310   \usebibmacro{author}%
1311   \setunit{\labelnamepunct}\newblock
1312   \usebibmacro{title}%
1313   \newunit
1314   \printlist{language}%
1315   \newunit\newblock
1316   \usebibmacro{byauthor}%
1317   \newunit\newblock
1318   \printfield{note}%
1319   \newunit\newblock
1320   \printfield{type}%
1321   \newunit
1322   \usebibmacro{institution+location+date}%
1323   \newunit\newblock
1324   \usebibmacro{chapter+pages}%
1325   \newunit
1326   \printfield{pagetotal}%
1327   \newunit\newblock
1328   \iftoggle{bbx:isbn}%
1329     {\printfield{isbn}}%
1330     {}%
1331   \newunit\newblock
1332   \usebibmacro{doi+eprint+url}%
1333   \newunit\newblock
1334   \usebibmacro{addendum+pubstate}%
1335   \newblock
1336   \iftoggle{bbx:related}%
1337     {\ifdefstring{\bbx@relatedformat}{semicolon}%
1338      {\setunit{\addsemicolon\space}}%
1339      {\setunit{\unspace\space}}%horrible trick
1340     \usebibmacro{related:init}%
1341 }
```

```
1341     \usebibmacro{related}%
1342     {}%
1343     \newunit\newblock
1344     \usebibmacro{pageref}%
1345     \usebibmacro{finentry}%
1346
1347 \DeclareBibliographyDriver{unpublished}{%
1348     \usebibmacro{bibindex}%
1349     \usebibmacro{begentry}%
1350     \usebibmacro{author}%
1351     \setunit{\labelnamepunct}\newblock
1352     \usebibmacro{title}%
1353     \newunit
1354     \printlist{language}%
1355     \newunit\newblock
1356     \usebibmacro{byauthor}%
1357     \newunit\newblock
1358     \printfield{howpublished}%
1359     \newunit\newblock
1360     \printfield{note}%
1361     \newunit\newblock
1362     \usebibmacro{location+date}%
1363     \newunit\newblock
1364     \iftoggle{bbx:url}
1365         {\usebibmacro{url+urldate}}
1366         {}%
1367     \newunit\newblock
1368     \usebibmacro{addendum+pubstate}%
1369     \newblock
1370     \iftoggle{bbx:related}
1371         {\ifdefstring{\bbx@relatedformat}{semicolon}%
1372          {\setunit{\addsemicolon\space}}%
1373          {\setunit{\unspace\space}}%horrible trick
1374          \usebibmacro{related:init}%
1375          \usebibmacro{related}%
1376          {}%
1377         \newunit\newblock
1378         \usebibmacro{pageref}%
1379         \usebibmacro{finentry}%
1380
1381 \DeclareBibliographyDriver{set}{%
1382     \protect\PackageWarningNoLine{biblatex-philosophy}{%
1383     \MessageBreak
1384     Entry type @set is not supported\MessageBreak
1385     by the 'biblatex-philosophy' styles.\MessageBreak
1386     All the @set entries will be ignored}%
1387
1388 % ripristina ordine nome cognome nelle voci inbook:full
1389 \renewbibmacro*{bybookauthor}{%
1390     \ifnamesequal{author}{bookauthor}%
1391     {}%
1392     {\printnames[default]{bookauthor}}}%
```

```
1393  
1394 \newbibmacro*{cross:maintitle+booktitle}{%  
1395     \iffieldundef{volume}  
1396         {}%  
1397         {\printfield{volume}}%  
1398         \printfield{part}%  
1399         \setunit{\addcolon\space}}%  
1400         \printfield{booktitle}}}}%  
1401  
1402 \newbibmacro*{xrefdata}{%  
1403     \usebibmacro{cross:maintitle+booktitle}}%  
1404     \newunit\newblock  
1405     \usebibmacro{byeditor+others}}%  
1406     \newunit\newblock  
1407     \printfield{edition}}%  
1408 %     \newunit  
1409 %     \iffieldundef{maintitle}  
1410 %         {\printfield{volume}}%  
1411 %         \printfield{part}}  
1412 %         {}%  
1413     \newunit  
1414     \printfield{volumes}}%  
1415     \newunit\newblock  
1416     \usebibmacro{series+number}}%  
1417     \newunit\newblock  
1418     \printfield{note}}%  
1419     \newunit\newblock  
1420     \usebibmacro{publisher+location+date}}%  
1421     \newunit\newblock  
1422     \usebibmacro{chapter+pages}}%  
1423     \newunit\newblock  
1424     \iftoggle{bbx:isbn}  
1425         {\printfield{isbn}}  
1426         {}%  
1427     \newunit\newblock  
1428     \usebibmacro{doi+eprint+url}}%  
1429     \newunit\newblock  
1430     \usebibmacro{addendum+pubstate:article-inbook-incoll}}%  
1431     \setunit{\bibpagerefpunct}\newblock  
1432     \iftoggle{bbx:related}  
1433         {\usebibmacro{related:init}}%  
1434         \usebibmacro{related}}  
1435         {}%  
1436     \newunit\newblock  
1437     \usebibmacro{pageref}}%  
1438     \usebibmacro{finentry}}  
1439  
1440 \newbibmacro*{crossrefdata}{%  
1441     \iffieldundef{maintitle}  
1442         {\printfield{volume}}%  
1443         \printfield{part}}  
1444         {}%
```

```

1445 \newunit\newblock
1446 \usebibmacro{chapter+pages}%
1447 \newunit\newblock
1448 \iftoggle{bbx:isbn}
1449   {\printfield{isbn}}
1450   {}%
1451 \newunit\newblock
1452 \usebibmacro{doi+eprint+url}%
1453 \setunit{\bibpagerefpunct}\newblock
1454 \iftoggle{bbx:related}
1455   {\usebibmacro{related:init}%
1456     \usebibmacro{related}%
1457   {}%
1458 \newunit\newblock
1459 \usebibmacro{pageref}%
1460 \usebibmacro{finentry}}

```

Experimental drivers for jurisprudence This feature is available for now only for Italian documents.

```

1461 %\DeclareFieldFormat[jurisprudence]{title}{#1}
1462 %\DeclareFieldFormat[jurisprudence]{pages}{#1}
1463 %\ExecuteBibliographyOptions[jurisprudence]{skipbib=true}%
1464 \DeclareFieldFormat[jurisdiction]{volume}{\RN{#1}}
1465 \DeclareFieldFormat[jurisdiction]{number}{\bibsstring{number}~{#1}}
1466 \DeclareFieldFormat[jurisdiction]{nameaddon}{%
1467   \ifinteger{#1}{\bibcpsstring{section}~\RN{#1}}{#1}}
1468 \DeclareFieldFormat[jurisdiction]{pages}{%
1469   \iffieldequalstr{bookpagination}{#1}{\mkpageprefix[bookpagination]{#1}}}
1470 \DeclareFieldFormat[jurisdiction]{title}{%
1471   \iffieldequalstr{entrysubtype}{international}{\emph{#1}}{#1}}
1472 \DeclareFieldFormat[jurisdiction]{notacomm}{nt\adddot{space}{#1}}

```

A new macro to manage authors of @jurisdiction entries.

```
1473 \newbibmacro*{juris:author}{}%
```

Use the default name format: “name surname”

```

1474 \DeclareNameAlias{sortname}{default}%
1475   \ifboolexpr{%
1476     test \ifuseauthor
1477     and
1478     not test {\ifnameundef{author}}}
1479 }%
1480 {%
1481   \iffieldequalstr{type}{conclusions}{%
1482     \printtext{Conclusioni dell'Avv\adddot{space} generale}%
1483     \setunit{\addspace}{}}
1484 \printnames{author}%
1485   \iffieldequalstr{authortype}{%
1486     {}%
1487     {\setunit{\addcomma\space}%
1488 \usebibmacro{authorstrg}}}
1489   {}%
1490 \iffieldequalstr{type}{conclusions}{%

```

```
1491     \setunit{\addspace}%
1492     \printtext{presentate il}%
1493     \setunit{\addspace}%
1494 }{%
1495     \setunit{\addcomma\space}%
1496     \iffieldundef{nameaddon}{}{%
1497     \printtext{\printfield{nameaddon}}%
1498     \setunit{\addcomma\space}}{%
1499 }%
1500     \printeventdate}
1501
1502 \newbibmacro*[addendum+pubstate:juris]{%
1503     \printfield{usera}%
1504     \notacomma
1505     \newunit\newblock
1506     \printfield{addendum}%
1507     \newunit\newblock
1508     \printfield{pubstate}%
1509     \ifdefstring{\bbx@origfields}{none}{}{%
1510         \newunit\newblock
1511         \usebibmacro{origdata:article-inbook}}%
1512         \newunit\newblock
1513         \usebibmacro{library}}
1514
1515 \DeclareBibliographyDriver{jurisdiction}{%
1516     \usebibmacro{bibindex}%
1517     \usebibmacro{begentry}%
1518     \usebibmacro{juris:author}%
1519     \setunit{\labelnamepunct}\newblock
1520     \usebibmacro{title}%
1521     \newunit\newblock
1522     \usebibmacro{series+number}%
1523     \printlist{language}%
1524     \newunit\newblock
1525     \usebibmacro{byauthor}%
1526     \newunit\newblock
1527     \iffieldundef{booktitle}{}{%
1528         \usebibmacro{in:}%
1529         \usebibmacro{maintitle+booktitle}%
1530         \newunit\newblock
1531         \printtext{%
1532             \printfield{labelyear}%
1533             \printfield{extrayear}%
1534             \usebibmacro{byeditor+others}%
1535             \newunit\newblock
1536             \printfield{edition}%
1537             \newunit
1538             \iffieldundef{maintitle}%
1539                 \printfield{volume}%
1540                 \printfield{part}%
1541             }%
1542             \newunit
1543             \printfield{volumes}%
1544 }
```

```

1543 \newunit\newblock
1544 \printfield{note}%
1545 \newunit\newblock
1546 \usebibmacro{publisher+location+date}%
1547 \newunit\newblock
1548 \usebibmacro{chapter+pages}%
1549 \newunit\newblock
1550 \iftoggle{bbx:isbn}
1551   {\printfield{isbn}}
1552   {}%
1553 \newunit\newblock
1554 \usebibmacro{doi+eprint+url}%
1555 \newunit\newblock
1556 \usebibmacro{addendum+pubstate:juris}%
1557 \newblock
1558 \iftoggle{bbx:related}
1559   {\ifdefstring{\bbx@relatedformat}{semicolon}%
1560     {\setunit{\addsemicolon\space}}%
1561     {\setunit{\unspace\space}}%horrible trick
1562   \usebibmacro{related:init}%
1563   \usebibmacro{related}{}%
1564   {}%
1565 \newunit\newblock
1566 \usebibmacro{pageref}%
1567 \usebibmacro{finentry}
```

Define new fields for @jurisdiction entry types and orig- fields mechanism:

```

1568 \ifblx@load@version@one
1569 \else
1570 \DeclareStyleSourcemap{
1571 \maps[datatype=bibtex]{
1572   \map{
1573     \step[fieldsource=court      , fieldtarget=author]
1574     \step[fieldsource=notacomm   , fieldtarget=usera]
1575     \step[fieldsource=section    , fieldtarget=nameaddon]
1576     \step[fieldsource=transdate   , fieldtarget=origdate]
1577     \step[fieldsource=transtitle  , fieldtarget=origtitle]
1578     \step[fieldsource=tranpublisher , fieldtarget=origpublisher]
1579     \step[fieldsource=translocation , fieldtarget=origlocation]
1580     \step[fieldsource=transbooktitle, fieldtarget=usera]
1581     \step[fieldsource=transnote    , fieldtarget=userb]
1582     \step[fieldsource=transpages   , fieldtarget=userc]
1583     \step[fieldsource=origbooktitle, fieldtarget=usera]
1584     \step[fieldsource=orignote    , fieldtarget=userb]
1585     \step[fieldsource=origpages   , fieldtarget=userc]
1586   }
1587 }
1588 }
1589 \fi
1590 \DeclareDataInheritance{**}{*}{*\noinherit{annotation}}
1591 \DeclareFieldAlias{jurisdiction}{usera}[jurisdiction]{notacomm}
```

```
1593 \DeclareFieldAlias[jurisdiction]{nameaddon}{jurisdiction}{section}
1594 \DeclareFieldAlias[jurisdiction]{author}{jurisdiction}{court}
1595
```

7.2 philosophy-classic.bbx

7.2.1 Initial settings

```
1596 \RequireBibliographyStyle{authoryear}
1597 \RequireBibliographyStyle{philosophy-standard}
1598
1599 \newtoggle{bbx:square}
1600 \newtoggle{bbx:nodate}
1601
1602 \DeclareBibliographyOption{square}[true]{%
1603   \settoggle{bbx:square}{\#1}}
1604 \DeclareBibliographyOption{nodate}[true]{%
1605   \settoggle{bbx:nodate}{\#1}}
1606
1607 \ExecuteBibliographyOptions{%
1608   nodate      = true,
1609   uniquename  = false,
1610   pagetracker = true,
1611   singletitle = false,
1612   square      = false,
1613   mergedate   = basic,
1614   dashed      = true,
1615 }
```

The `classic` and `modern` styles redefine the `relateddate` and `commarelateddate` macros because the date have to be printed after the name of the author/editor. In the list of shorthands we need a standard entry, with the date at the end and no date after the name of the author/editor so we overwrite these macros locally:

```
1616 \AtBeginShorthands{%
1617 \togglefalse{bbx:annotation}%
1618 \renewcommand{\labelnamepunct}{\addcomma\space}%
1619 \renewbibmacro*[relateddate]{%
1620   \setunit{\addspace}%
1621   \printdate}%
1622 \renewbibmacro*[commarelateddate]{%
1623   \setunit{\addcomma\space}%
1624   \printdate}%
1625 \DeclareCiteCommand{\bbx@crossref@inbook}
1626   {}%
1627   {\iffieldundef{shorthand}{%
1628     \usebibmacro{citeindex}%
1629     \ifuseeditor{%
1630       \ifthenelse{\value{listtotal}=2}{%
1631         {\printnames[][-\value{maxnamesincross}]{\labelname}}%
1632         {\printnames[][-\value{minnamesincross}]{\labelname}}}%
1633       \usebibmacro{labeltitle}%
1634     } \setunit{\addspace}%
1635   }%
```

```

1635     \usebibmacro{date+extrayear:crossref}%
1636     {\usebibmacro{cite:shorthand}}%
1637     {}%
1638     {}%
1639 \DeclareCiteCommand{\bbx@crossref@incollection}%
1640     {}%
1641     {\iffieldundef{shorthand}{%
1642       \usebibmacro{citeindex}%
1643       \ifuseeditor{%
1644         \ifthenelse{\value{listtotal}=2}{%
1645           {\printnames[][-\value{maxnamesincross}]{labelname}}%
1646           {\printnames[][-\value{minnamesincross}]{labelname}}}}%
1647         {\usebibmacro{labeltitle}}%
1648         \setunit*{\addspace}%
1649         \usebibmacro{date+extrayear:crossref}%
1650         {\usebibmacro{cite:shorthand}}%
1651     }{}%
1652     {}%
1653 \newbibmacro*[date+extrayear:crossref]{%
1654   \begingroup%
1655     \clearfield{month}%
1656     \clearfield{day}%
1657     \ifboolexpr{%
1658       test {\iffieldundef{date}}
1659       and
1660       test {\iffieldundef{year}}
1661     }{%
1662       {\iftoggle{\bbx:nodate}{\printtext[parens]{%
1663         \midsentence\bibstring{nodate}}}{}}%
1664       {\printtext[parens]{\printdateextra}}%
1665       \endgroup}%
1666 \newbibmacro*[date+extrayear]{%
1667 }%
1668 %
1669 \AtBeginDocument{%
1670   \iftoggle{\bbx:square}{%
1671     {\renewcommand{\bibopenparen}{\bibopenbracket}%
1672      \renewcommand{\bibcloseparen}{\bibclosebracket}}%
1673     {}%
1674   \setcounter{maxnamesincross}{\value{maxnames}}%
1675   \setcounter{minnamesincross}{\value{minnames}}%
1676 }%
1677 %
1678 \AtEveryBibitem{%
1679   \iffieldequalstr{entrysubtype}{classic}{%
1680     \togglefalse{\bbx:nodate}}}%
1681

```

7.2.2 New macros

Renew the bibliography macro 'relateddate' to delete the date at the end of the entry:

```

1682 \renewbibmacro*[relateddate]{}
1683 \renewbibmacro*[commarelateddate]{}

```

Dates

```

1684 \renewbibmacro*{issue+date}{%
1685   \ifboolexpr{%
1686     test {\iffieldundef{issue}}
1687     and
1688     test {\iffieldundef{month}}
1689   }%
1690   {}%
1691   {\ifdefstring{\bbx@volnumformat}{parens}{%
1692     \printtext{%
1693       \printfield{issue}\setunit*{\addspace}%
1694       \printdate}}%
1695     {\printtext[pureparens]{%
1696       \printfield{issue}\setunit*{\addspace}%
1697       \printdate}}%
1698   \newunit}%

```

Delete “month” from `\printdateextra` to print open ranges such as: “1968–”:

```

1699 \renewbibmacro*{date+extrayear}{%
1700   \begingroup%
1701   \clearfield{month}%
1702   \clearfield{day}%
1703   \ifboolexpr{%
1704     test {\iffieldundef{date}}
1705     and
1706     test {\iffieldundef{year}}
1707   }%
1708   {\iftoggle{\bbx:nodate}{\printtext[parens]{%
1709     \midsentence\bibstring{nodate}}}{}}%
1710   {\printtext[parens]{\printdateextra}}%
1711   \endgroup}%

```

Authors and editors

```

1712 \renewbibmacro*{author}{%
1713   \ifboolexpr{%
1714     test \ifuseauthor
1715     and
1716     not test {\ifnameundef{author}}}
1717 }%
1718   {\usebibmacro{bbx:dashcheck}%
1719     {\bibnamedash}%
1720     {\usebibmacro{bbx:savehash}%
1721       \printnames{author}%
1722       \iffieldundef{nameaddon}{}%
1723       {\setunit{\addspace}%
1724         \printtext[brackets]{\printfield{nameaddon}}}}%
1725 \iffieldundef{authortype}%
1726   {\setunit{\addspace}}%
1727   {\setunit{\addcomma\space}}%
1728   \iffieldundef{authortype}%
1729   {}%

```

```

1730      {\usebibmacro{authorstrg}}%
1731 \setunit{\addspace}}}}%
1732     {\global\undef\bbx@lasthash}%
1733     \usebibmacro{labeltitle}}%
1734     \setunit*{\addspace}}}}%
1735 \usebibmacro{date+extrayear}}}}%
1736
1737 \renewbibmacro*{editor}{%
1738   \usebibmacro{bbx:editor}{editorstrg}}}}%
1739 \renewbibmacro*{editor+others}{%
1740   \usebibmacro{bbx:editor}{editor+othersstrg}}}}%
1741 \renewbibmacro*{bbx:editor}[1]{%
1742   \ifboolexpr{%
1743     test \ifuseeditor
1744     and
1745     not test {\ifnameundef{editor}}}
1746 }}}%
1747   {\usebibmacro{bbx:dashcheck}}%
1748     {\bibnamedash}}%
1749     {\printnames{editor}}}}%
1750 \setunit{\addspace}}%
1751 \usebibmacro{bbx:savehash}}}}%
1752   \usebibmacro{#1}}%
1753   \clearname{editor}}}}%
1754   \setunit{\addspace}}}}%
1755   {\global\undef\bbx@lasthash}%
1756   \usebibmacro{labeltitle}}%
1757   \setunit*{\addspace}}}}%
1758 \usebibmacro{date+extrayear}}}}%

```

7.2.3 Internal commands for crossreferences

```

1759 \DeclareCiteCommand{\bbx@crossref@inbook}}%
1760   {}}}%
1761   {\usebibmacro{citeindex}}%
1762   \ifuseeditor{}%
1763     \ifthenelse{\value{listtotal}=2}{%
1764       {\printnames[] [-\value{maxnamesincross}]{labelname}}}}%
1765       {\printnames[] [-\value{minnamesincross}]{labelname}}}}}}%
1766     {\usebibmacro{labeltitle}}}}%
1767     \setunit*{\addspace}}%
1768     \usebibmacro{date+extrayear}}}}%
1769   {}}}%
1770   {}}}%
1771
1772 \DeclareCiteCommand{\bbx@crossref@incollection}}%
1773   {}}}%
1774   {\usebibmacro{citeindex}}%
1775   \ifuseeditor{}%
1776     \ifthenelse{\value{listtotal}=2}{%
1777       {\printnames[] [-\value{maxnamesincross}]{labelname}}}}%
1778       {\printnames[] [-\value{minnamesincross}]{labelname}}}}}}%

```

```

1779      {\usebibmacro{labeltitle}}%
1780      \setunit*{\addspace}%
1781      \usebibmacro{date+extrayear}}%
1782  {}%
1783  {}%

```

The `restoreclassic` option is redundant for the `philosophy-classic` style. Anyway it is defined to avoid error messages:

```

1784 \define@key{blx@bib1}{restoreclassic}[]{}
1785 \define@key{blx@bib2}{restoreclassic}[true]{}

```

7.2.4 The `nodate` option for `\printbibliography`

```

1786 \define@key{blx@bib1}{nodate}[]{}%
1787 \define@key{blx@bib2}{nodate}[true]{%
1788   \ifstreq{\#1}{false}{%
1789     \togglefalse{bbx:nodate}%
1790   }{}%

```

7.3 `philosophy-modern.bbx`

7.3.1 Initial settings

```

1791 \RequireBibliographyStyle{philosophy-classic}

```

The `modern` style has only one specific option which is turned off by default:

```

1792 \newtoggle{bbx:yearleft}%
1793 \DeclareBibliographyOption{yearleft}[true]{%
1794   \settoggle{bbx:yearleft}{\#1}%
1795 \ExecuteBibliographyOptions{%
1796   yearleft=false}

```

7.3.2 New lengths

```

1797 \newlength{\yeartitle}%
1798 \newlength{\postnamesep}%
1799 \setlength{\yeartitle}{0.8em}%
1800 \setlength{\postnamesep}{0.5ex plus 2pt minus 1pt}%
1801 \setlength{\bibitemsep}{\postnamesep}%
1802 \setlength{\bibnamesep}{1.5ex plus 2pt minus 1pt}%
1803 \setlength{\bibhang}{4\parindent}%
1804 %
1805 \AtBeginBibliography{%
1806   \iftoggle{bbx:yearleft}{%
1807     \setlength{\yeartitle}{\fill}%
1808   }{}%

```

7.3.3 New commands

```

1809 \newcommand{\postsep}{\par\nobreak\vskip\postnamesep}%
1810   \hskip-\bibhang\ignorespaces}%
1811 \renewcommand{\labelnamepunct}{}%
1812 %
1813 \AtBeginShorthands{%
1814   \renewcommand{\postsep}{}%
1815   \renewcommand{\labelnamepunct}{\newunitpunct}}

```

7.3.4 New macros

Dates

```

1816 \renewbibmacro*{date+extrayear}{%
1817     \begingroup%
1818     \clearfield{month}%
1819     \clearfield{day}%
1820     \makebox[\bibhang][r]{\printtext{%
1821         \ifboolexpr{%
1822             test {\iffieldundef{date}}%
1823             and%
1824             test {\iffieldundef{year}}%
1825         }%
1826         {\iftoggle{bbx:nodate}{\printtext{%
1827             \midsentence{\bibstring{nodate}}}}{}}%
1828         {\printtext{\printdateextra}}%
1829         \hskip\yeartitle}}%
1830     \endgroup}%
1831
1832 \renewbibmacro*{labeltitle}{%
1833     \iffieldundef{label}%
1834     {\iffieldundef{shorttitle}%
1835         {\printfield{title}\clearfield{title}}%
1836         {\printfield[title]{shorttitle}}}}%
1837     {\printtext{\printfield{label}}%
1838 \postsep}}
```

Authors and editors

```

1839 \renewbibmacro*{author}{%
1840     \ifboolexpr{%
1841         test \ifuseauthor%
1842         and%
1843         not test {\ifnameundef{author}}%
1844     }%
1845     {\usebibmacro{bbx:dashcheck}%
1846         {}%
1847         {\usebibmacro{bbx:savehash}%
1848             \printnames{author}%
1849             \iffieldundef{nameaddon}{}%
1850             {\setunit{\addspace}%
1851                 \printtext[brackets]{\printfield{nameaddon}}}}%
1852             \iffieldundef{authortype}%
1853             {}%
1854             {\setunit{\addcomma\space}}%
1855             \usebibmacro{authorstrg}%
1856         \postsep}}%
1857         {\global\undef\bbx@lasthash%
1858         \usebibmacro{labeltitle}%
1859         \setunit*\addspace}%
1860     \usebibmacro{date+extrayear}%
1861
```

```

1862 \renewbibmacro*{editor}{%
1863   \usebibmacro{bbx:editor}{editorstrg}}%
1864 \renewbibmacro*{editor+others}{%
1865   \usebibmacro{bbx:editor}{editor+othersstrg}}%
1866 \renewbibmacro*{bbx:editor}[1]{%
1867   \ifboolexpr{%
1868     test \ifuseeditor
1869     and
1870     not test {\ifnameundef{editor}}}
1871 }%
1872   {\usebibmacro{bbx:dashcheck}}%
1873   {}%
1874   {\printnames{editor}}%
1875   \postsep%ADD
1876   \usebibmacro{bbx:savehash}}}}%
1877   {\global\undef\bbx@lasthash}%
1878   \usebibmacro{labeltitle}}}}%
1879 \usebibmacro{date+extrayear}}%
1880   \iffieldundef{label}}}}%
1881   {\usebibmacro{#1}}%
1882   \clearname{editor}}%
1883   \printtext{\addcomma\space}}}}%

```

7.3.5 Internal commands for crossreferences

```

1884 \DeclareCiteCommand{\bbx@crossref@inbook}{%
1885   {}%
1886   {\usebibmacro{citeindex}}%
1887   \ifuseeditor{%
1888     \ifthenelse{\value{listtotal}=2}{%
1889       {\printnames[][-\value{maxnamesincross}]{labelname}}%
1890       {\printnames[][-\value{minnamesincross}]{labelname}}}}%
1891     \usebibmacro{labeltitle}}}}%
1892   \setunit*{\addspace}}%
1893   \usebibmacro{classic:date+extrayear}}}}%
1894 {}%
1895 {}%
1896
1897 \DeclareCiteCommand{\bbx@crossref@incollection}{%
1898   {}%
1899   {\usebibmacro{citeindex}}%
1900   \ifuseeditor{%
1901     \ifthenelse{\value{listtotal}=2}{%
1902       {\printnames[][-\value{maxnamesincross}]{labelname}}%
1903       {\printnames[][-\value{minnamesincross}]{labelname}}}}%
1904     \usebibmacro{labeltitle}}}}%
1905   \setunit*{\addspace}}%
1906   \usebibmacro{classic:date+extrayear}}}}%
1907 {}%
1908 {}%
1909
1910 \newbibmacro*{classic:date+extrayear}{%

```

```

1911 \begingroup%
1912   \clearfield{month}%
1913   \clearfield{day}%
1914 \ifboolexpr{%
1915   test {\iffieldundef{date}}
1916   and
1917   test {\iffieldundef{year}}
1918 }%
1919   {\iftoggle{bbx:nodate}{\printtext[parens]{%
1920     \midsentence\bibstring{nodate}}}{}}%
1921   {\printtext[parens]{%
1922 \printfield{labelyear}%
1923 \printfield{extrayear}}}%
1924 \endgroup}%

```

7.3.6 The restoreclassic option

```

1925 \define@key{blx@bib1}{restoreclassic}{}{%
1926 \define@key{blx@bib2}{restoreclassic}[true]{%
1927   \ifstreq{\#1}{true}{%
1928     \setlength{\bibhang}{\parindent}%
1929     \renewcommand{\labelnamepunct}{\newunitpunct}%
1930     \renewbibmacro*{date+extrayear}{%
1931       \begingroup%
1932         \clearfield{month}%
1933         \clearfield{day}%
1934       \ifboolexpr{%
1935         test {\iffieldundef{date}}
1936         and
1937         test {\iffieldundef{year}}
1938 }%
1939         {\iftoggle{bbx:nodate}{\printtext[parens]{%
1940           \midsentence\bibstring{nodate}}}{}}%
1941         {\printtext[parens]{\printdateextra}}%
1942       \endgroup}%
1943     \renewbibmacro*{author}{%
1944       \ifboolexpr{%
1945         test \ifuseauthor
1946         and
1947         not test {\ifnameundef{author}}}
1948     }%
1949       {\usebibmacro{bbx:dashcheck}%
1950         {\bibnamedash}%
1951         {\usebibmacro{bbx:savehash}%
1952           \printnames{author}%
1953           \iffieldundef{nameaddon}{}%
1954           {\setunit{\addspace}%
1955             \printtext[brackets]{\printfield{nameaddon}}}%
1956         \iffieldundef{authortype}%
1957           {\setunit{\addspace}}%
1958           {\setunit{\addcomma\space}}%
1959           \iffieldundef{authortype}%
1960             {}}%

```

```

1961      {\usebibmacro{authorstrg}%
1962 \setunit{\addspace}}}%
1963      {\global\undef\bbx@lasthash%
1964      \usebibmacro{labeltitle}%
1965      \setunit*{\addspace}}%
1966      \usebibmacro{date+extrayear}%
1967 \renewbibmacro*{editor}{%
1968      \usebibmacro{bbx:editor}{editorstrg}%
1969 \renewbibmacro*{editor+others}{%
1970      \usebibmacro{bbx:editor}{editor+othersstrg}%
1971 \renewbibmacro*{bbx:editor}[1]{%
1972      \ifboolexpr{%
1973          test \ifuseeditor
1974          and
1975          not test {\ifnameundef{editor}}}
1976    }%
1977      {\usebibmacro{bbx:dashcheck}%
1978        {\bibnamedash}%
1979        {\printnames{editor}}%
1980 \setunit{\addspace}%
1981 \usebibmacro{bbx:savehash}%
1982      \usebibmacro{#1}%
1983      \clearname{editor}%
1984      \setunit{\addspace}}%
1985      {\global\undef\bbx@lasthash%
1986      \usebibmacro{labeltitle}%
1987      \setunit*{\addspace}}%
1988      \usebibmacro{date+extrayear}%
1989 \renewbibmacro*{labeltitle}{%
1990      \iffieldundef{label}%
1991        {\iffieldundef{shorttitle}%
1992          {\printfield{title}%
1993          \clearfield{title}}%
1994          {\printfield[title]{shorttitle}}}}%
1995        {\printfield{label}}}%
1996    }{}}

```

7.4 philosophy-verbose.bbx

7.4.1 Initial settings

```

1997 \RequireBibliographyStyle{authortitle}
1998 \RequireBibliographyStyle{philosophy-standard}
1999 \AtBeginShorthands{%

```

The annotation field is omitted in the list of shorthands:

```
2000 \togglefalse{bbx:annotation}
```

In the list of shorthands we always use the shorthand for the cross-referenced entries:

```

2001 \DeclareCiteCommand{\bbx@crossref@inbook}%
2002 {}%
2003 {\iffieldundef{shorthand}%
2004   {\usebibmacro{inbook:full}}%
2005   {\usebibmacro{cite:shorthand}}}%

```

```

2006  {}%
2007  {}%
2008 \DeclareCiteCommand{\bbx@crossref@incollection}%
2009  {}%
2010  {\iffieldundef{shorthand}%
2011    {\usebibmacro{incollection:full}}%
2012    {\usebibmacro{cite:shorthand}}}%
2013  {}%
2014  {}%
2015 }

```

Authors and editors

```

2016 \renewbibmacro*{author}{%
2017   \ifboolexpr{%
2018     test \ifuseauthor
2019     and
2020     not test {\ifnameundef{author}}}
2021 }%
2022   {\usebibmacro{bbx:dashcheck}%
2023     {\bibnamedash}%
2024     {\printnames{author}%
2025       \iffieldundef{nameaddon}{}%
2026       {\setunit{\addspace}%
2027         \printtext[brackets]{\printfield{nameaddon}}}}%
2028 \setunit{\addcomma\space}%
2029 \usebibmacro{bbx:savehash}%
2030   \usebibmacro{authorstrg}%
2031   {\global\undef\bbx@lasthash}%
2032
2033 \renewbibmacro*{editor}{%
2034   \usebibmacro{bbx:editor}{editorstrg}%
2035 \renewbibmacro*{editor+others}{%
2036   \usebibmacro{bbx:editor}{editor+othersstrg}%
2037 \renewbibmacro*{bbx:editor}[1]{%
2038   \ifboolexpr{%
2039     test \ifuseeditor
2040     and
2041     not test {\ifnameundef{editor}}}
2042 }%
2043   {\usebibmacro{bbx:dashcheck}%
2044     {\bibnamedash}%
2045     {\printnames{editor}%
2046 \setunit{\addspace}#MOD#
2047     \usebibmacro{bbx:savehash}%
2048   \usebibmacro{#1}%
2049   \clearname{editor}%
2050   {\global\undef\bbx@lasthash}}%

```

7.4.2 Internal commands for crossreferences

```

2051 \newbibmacro*{nodash:author}{%
2052   \ifboolexpr{%

```

```
2053     test \ifuseauthor
2054     and
2055     not test {\ifnameundef{author}}
2056 }%
2057   {\printnames{author}%
2058     \iffieldundef{nameaddon}{\%}
2059     {\setunit{\addspace}%
2060      \printtext[brackets]{\printfield{nameaddon}}\%}
2061 \setunit{\addcomma\space}%
2062   \usebibmacro{authorstrg}\%}
2063   {\global\undef\bbx@lasthash}}
2064
2065 \newbibmacro*{nodash:editor+others}{%
2066   \usebibmacro{nodash:bbx:editor}{editor+othersstrg}\%}
2067 \newbibmacro*{nodash:bbx:editor}[1]{%
2068   \ifboolexpr{%
2069     test \ifuseeditor
2070     and
2071     not test {\ifnameundef{editor}}}
2072 }%
2073   {\printnames{editor}%
2074 \setunit{\addspace}%
2075   \usebibmacro{\#1}\%
2076   \clearname{editor}\%}
2077   {\global\undef\bbx@lasthash}}
2078
2079 \newbibmacro*{nodash:author/editor+others/translator+others}{%
2080   \ifboolexpr{%
2081     test \ifuseauthor
2082     and
2083     not test {\ifnameundef{author}}}
2084 }%
2085   {\usebibmacro{nodash:author}}
2086   {\ifboolexpr{%
2087     test \ifuseeditor
2088     and
2089     not test {\ifnameundef{editor}}}
2090 }%
2091   {\usebibmacro{nodash:editor+others}}
2092   {\usebibmacro{translator+others}}\}}
2093
2094 \newbibmacro*{usedriver:book}{%
2095   \usebibmacro{bibindex}\%
2096   \usebibmacro{begentry}\%
2097   \usebibmacro{nodash:author/editor+others/translator+others}\%
2098   \setunit{\labelnamepunct}\newblock
2099   \usebibmacro{maintitle+title}\%
2100   \newunit
2101   \printlist{language}\%
2102   \newunit\newblock
2103   \usebibmacro{byauthor}\%
2104   \newunit\newblock
```

```
2105 \usebibmacro{byeditor+others}%
2106 \newunit\newblock
2107 \printfield{edition}%
2108 \newunit
2109 \printfield{volumes}%
2110 \newunit\newblock
2111 \usebibmacro{series+number}%
2112 \newunit\newblock
2113 \printfield{note}%
2114 \newunit\newblock
2115 \usebibmacro{publisher+location+date}%
2116 \newunit
2117 \iffieldundef{maintitle}
2118   {\printfield{volume}%
2119     \printfield{part}%
2120   {}%
2121 \newunit\newblock
2122 \usebibmacro{chapter+pages}%
2123 \newunit
2124 \printfield{pagetotal}%
2125 \newunit\newblock
2126 \iftoggle{bbx:isbn}
2127   {\printfield{isbn}%
2128   {}%
2129 \newunit\newblock
2130 \usebibmacro{doi+eprint+url}%
2131 \newunit\newblock
2132 \usebibmacro{addendum+pubstate}%
2133 \newblock
2134 \iftoggle{bbx:related}
2135   {\ifdefstring{\bbx@relatedformat}{semicolon}%
2136     {\setunit{\addsemicolon\space}}%
2137     {\setunit{\unspace\space}}%\horrible trick
2138   \usebibmacro{related:init}%
2139     \usebibmacro{related}{}%
2140   {}%
2141 \newunit\newblock
2142 \usebibmacro{pageref}%
2143 }
2144 \newbibmacro*{usedriver:collection}%
2145   \usebibmacro{bibindex}%
2146   \usebibmacro{begentry}%
2147   \usebibmacro{nodash:editor+others}%
2148   \setunit{\labelnamepunct}\newblock
2149   \usebibmacro{maintitle+title}%
2150   \newunit
2151   \printlist{language}%
2152   \newunit\newblock
2153   \usebibmacro{byeditor+others}%
2154   \newunit\newblock
2155   \printfield{edition}%
2156   \newunit
```

```
2157 \iffieldundef{maintitle}%
2158   {\printfield{volume}%
2159     \printfield{part}%
2160   {}%
2161 \newunit
2162 \printfield{volumes}%
2163 \newunit\newblock
2164 \usebibmacro{series+number}%
2165 \newunit\newblock
2166 \printfield{note}%
2167 \newunit\newblock
2168 \usebibmacro{publisher+location+date}%
2169 \newunit\newblock
2170 \usebibmacro{chapter+pages}%
2171 \newunit
2172 \printfield{pagetotal}%
2173 \newunit\newblock
2174 \iftoggle{bbx:isbn}%
2175   {\printfield{isbn}%
2176   {}%
2177 \newunit\newblock
2178 \usebibmacro{doi+eprint+url}%
2179 \newunit\newblock
2180 \usebibmacro{addendum+pubstate}%
2181 \newblock
2182 \iftoggle{bbx:related}%
2183   {\ifdefstring{\bbx@relatedformat}{semicolon}%
2184     {\setunit{\addsemicolon\space}}%
2185     {\setunit{\unspace\space}}%\horrible trick
2186   \usebibmacro{related:init}%
2187   \usebibmacro{related}{}%
2188   {}%
2189 \newunit\newblock
2190 \usebibmacro{pageref}%
2191 }
2192 \DeclareCiteCommand{\bbx@crossref@inbook}%
2193 {}%
2194 \ifciteseen{%
2195   \ifthenelse{\value{listtotal}=2}%
2196     {\printnames[][-\value{maxnamesincross}]{labelname}}%
2197     {\printnames[][-\value{minnamesincross}]{labelname}}%
2198   \setunit*{\addcomma\space}\printtext{%
2199     \printfield[citetitle]{labeltitle}%
2200     \iftoggle{cbx:commacit}{\setunit{\addcomma\space}}%
2201     \setunit{\addspace\midsentence}{}%
2202     \bibstring{cited}{}%
2203     {\DeclareNameAlias{sortname}{default}}%
2204     \usebibmacro{usedriver:book}{}%
2205   {}%
2206   {}%
2207 \DeclareCiteCommand{\bbx@crossref@incollection}%
2208   {}%
```

```

2209  {\ifciteseen{%
2210  \ifthenelse{\value{listtotal}=2}{%
2211    {\printnames[] [-\value{maxnamesincross}]{labelname}}{%
2212    {\printnames[] [-\value{minnamesincross}]{labelname}}{%
2213      \setunit{\addspace}{%
2214        \usebibmacro{editorstrg}}{%
2215        \setunit*{\addcomma\space}\printtext{%
2216          \printfield[citetitle]{labeltitle}}{%
2217            \iftoggle{cbx:commacit}{\setunit{\addcomma\space}}{%
2218              {\setunit{\addspace\midsentence}}{%
2219                \bibstring{cited}}}}{%
2220              {\Declarnamelistalias{sortname}{default}}{%
2221                \usebibmacro{usedriver:collection}}}}{%
2222              {}{%
2223              {}}}{%

```

7.5 philosophy-classic.cbx

7.5.1 Initial settings

```

2224 \RequireCitationStyle{authoryear-comp}
2225
2226 \newtoggle{cbx:scauthorscite}
2227
2228 \DeclareBibliographyOption{scauthorscite}[true]{%
2229   \settoggle{cbx:scauthorscite}{#1}}
2230
2231 \ExecuteBibliographyOptions{%
2232   scauthorscite = false,
2233   citetracker = true,
2234 }
2235
2236 \AtEveryCite{%
2237   \iftoggle{cbx:scauthorscite}{%
2238     {\let\mkbibnamelast\mkbibsc{%
2239       \let\mkbibnamefirst\mkbibsc{%
2240         \let\mkbibnameprefix\mkbibsc{%
2241           \let\mkbibnameaffix\mkbibsc{%
2242             {}}}}}{%
2243 \Declarnamelistalias{labelname}{%
2244 \bibhyperref{%
2245   \ifcase\value{uniquename}{%
2246     \usebibmacro{name:last}{#1}{#3}{#5}{#7}{%
2247     \or
2248       \ifuseprefix
2249         {\usebibmacro{name:first-last}{#1}{#4}{#5}{#8}}{%
2250           {\usebibmacro{name:first-last}{#1}{#4}{#6}{#8}}}{%
2251     \or
2252       \usebibmacro{name:first-last}{#1}{#3}{#5}{#7}{%
2253     \fi
2254     \usebibmacro{name:andothers}}}}{%
2255 %%%%
2256

```

```

2257 \newcommand{\switchclass}[2]{%
2258   \iffieldequalstr{entrysubtype}{classic}%
2259     {\usebibmacro{#1}}%
2260     {\usebibmacro{#2}}}

```

7.5.2 Author-title macros

Import the :AT macros from the authortitle-comp.cbx file.

```

2261 \newbibmacro*[cite:init:AT]{%
2262   \ifnumless{\value{multicitecount}}{2}
2263     {\global\boolfalse{cbx:parens}%
2264      \global\undef\cbx@lasthash}%
2265     {\iffieldundef{prenote}%
2266       {}%
2267       {\global\undef\cbx@lasthash}}}
2268 
2269 \newbibmacro*[cite:reinit:AT]{%
2270   \global\undef\cbx@lasthash}
2271 
2272 \newbibmacro*[cite:AT]{%
2273   \iffieldundef{shorthand}%
2274     {\iffieldequals{namehash}{\cbx@lasthash}%
2275      {\setunit{\compcitedelim}}%
2276      {\ifnameundef{labelname}%
2277        {}%
2278        {\printnames{labelname}}%
2279        \setunit{\nametitledelim}}%
2280      \savefield{namehash}{\cbx@lasthash}}%
2281   \usebibmacro{cite:title:AT}%
2282   {\usebibmacro{cite:shorthand}%
2283    \usebibmacro{cite:reinit:AT}}%
2284   \setunit{\multicitedelim}}
2285 
2286 \newbibmacro*[citetitle:AT]{%
2287   \iffieldundef{shorthand}%
2288     {\usebibmacro{cite:title:AT}}%
2289     {\usebibmacro{cite:shorthand}}%
2290   \setunit{\multicitedelim}}
2291 
2292 \newbibmacro*[textcite:AT]{%
2293   \iffieldequals{namehash}{\cbx@lasthash}%
2294     {\setunit{\compcitedelim}}%
2295     {\ifnameundef{labelname}%
2296       {}%
2297       {\printnames{labelname}}%
2298       \setunit{%
2299         \global\booltrue{cbx:parens}%
2300         \addspace\bibopenparen}}%
2301       \savefield{namehash}{\cbx@lasthash}}%
2302   \ifnumequal{\value{citecount}}{1}%
2303     {\usebibmacro{prenote}}%
2304     {}%
2305   \iffieldundef{shorthand}}

```

```

2306  {\usebibmacro{cite:title} }%
2307  {\iftoggle{cbx:shorthandintro}{%
2308    \ifciteseen{%
2309      \usebibmacro{cite:shorthand} }%
2310      {\usebibmacro{shorthandintro}} }%
2311    {\usebibmacro{cite:shorthand}} }%
2312  \setunit{%
2313    \ifbool{cbx:parens}{%
2314      {\bibcloseparen\global\boolfalse{cbx:parens}}%
2315    }%
2316    \multicitedelim} }
2317
2318 \newbibmacro*[cite:title:AT]{%
2319   \printtext[bibhyperref]{\printfield[citetitle]{labeltitle}}}
2320
2321 \newbibmacro*[textcite:postnote:AT]{%
2322   \ifnameundef{labelname}{%
2323     \setunit{%
2324       \global\booltrue{cbx:parens}%
2325       \addspace\bibopenparen}%
2326     \setunit{\postnotedelim}} }%
2327   \printfield[postnote]{%
2328   \ifthenelse{\value{multicitecount}=\value{multicitetotal}}{%
2329     \setunit{} }%
2330     \printtext{%
2331       \ifbool{cbx:parens}{%
2332         {\bibcloseparen\global\boolfalse{cbx:parens}}%
2333       } }%
2334     \setunit{%
2335       \ifbool{cbx:parens}{%
2336         {\bibcloseparen\global\boolfalse{cbx:parens}}%
2337       }%
2338       \multicitedelim}} }%

```

7.5.3 Author-year macros

```

2339 \newbibmacro*[cite:init:AY]{%
2340   \ifnumless{\value{multicitecount}}{2}{%
2341     {\global\boolfalse{cbx:parens}}%
2342     \global\undef\cbx@lasthash
2343     \global\undef\cbx@lastyear
2344     {\iffieldundef{prenote}{%
2345       {} }%
2346       {\global\undef\cbx@lasthash
2347     \global\undef\cbx@lastyear}} }%
2348
2349 \newbibmacro*[cite:reinit:AY]{%
2350   \global\undef\cbx@lasthash
2351   \global\undef\cbx@lastyear}
2352
2353 \newbibmacro*[cite:AY]{%
2354   \iffieldundef{shorthand}{%

```

```
2355  {\usebibmacro{cite:noshorthand}}%
2356  {\iftoggle{cbx:shorthandintro}{%
2357  {%
2358  \ifciteseen{\usebibmacro{cite:shorthand}}%
2359  {\usebibmacro{cite:noshorthand}}%
2360  \usebibmacro{shorthandintro}}%
2361  }%
2362  {\usebibmacro{cite:shorthand}}%
2363  \usebibmacro{cite:reinit:AY}}%
2364  \setunit{\multicitedelim}
2365
2366 \newbibmacro*{textcite:AY}{%
2367  \iffieldequals{namehash}{\cbx@lasthash}{%
2368  {\iffieldundef{shorthand}{\noshorthand}%
2369  {\ifthenelse{\iffieldequals{labelyear}{\cbx@lastyear}\AND
2370  {\(\value{multicitecount}=0\OR\iffieldundef{postnote})}}{%
2371  {\setunit{\addcomma}%
2372  \usebibmacro{cite:extrayear}}%
2373  {\setunit{\compcitedelim}%
2374  \usebibmacro{cite:labelyear+extrayear}}%
2375  \savefield{labelyear}{\cbx@lastyear}}}}%
2376  {\setunit{\compcitedelim}\shorthand}%
2377  \iftoggle{cbx:shorthandintro}{%
2378  {\ifciteseen{%
2379  {\usebibmacro{cite:shorthand}}%
2380  {\ifthenelse{\iffieldequals{labelyear}{\cbx@lastyear}\AND
2381  {\(\value{multicitecount}=0\OR\iffieldundef{postnote})}}{%
2382  {\setunit{\addcomma}%
2383  \usebibmacro{cite:extrayear}}%
2384  {\setunit{\compcitedelim}%
2385  \usebibmacro{cite:labelyear+extrayear}}%
2386  \savefield{labelyear}{\cbx@lastyear}}}}%
2387  {\usebibmacro{shorthandintro}}}}%
2388  {\usebibmacro{cite:shorthand}}%
2389  \global\undef\cbx@lastyear}}}}%
2390  {\ifnameundef{labelname}}%
2391  {\iffieldundef{shorthand}\shorthand{%
2392  {\usebibmacro{cite:label}}%
2393  \setunit{%
2394  \global\booltrue{cbx:parens}%
2395  \addspace\bibopenparen}}%
2396  \ifnumequal{\value{citecount}}{1}{%
2397  {\usebibmacro{prenote}}%
2398  {\usebibmacro{cite:shorthand}}}}%
2399  \usebibmacro{cite:labelyear+extrayear}}}}%
2400  {\iftoggle{cbx:shorthandintro}{%
2401  {\ifciteseen\shorthand{%
2402  {\usebibmacro{cite:shorthand}}}}%
2403  {\usebibmacro{cite:label}}}}%
2404  \setunit{%
2405  \global\booltrue{cbx:parens}%
2406  \addspace\bibopenparen}}}
```

```

2407 \ifnumequal{\value{citecount}}{1}%
2408   {\usebibmacro{prenote}%
2409    {\usebibmacro{cite:shorthand}%
2410     \usebibmacro{cite:labelyear+extrayear}%
2411     \usebibmacro{shorthandintro}{}%
2412     {\usebibmacro{cite:shorthand}{}%
2413      {\printnames{labelname}%
2414 \setunit{%
2415   \global\booltrue{cbx:parens}%
2416   \addspace\bibopenparen}%
2417 \ifnumequal{\value{citecount}}{1}%
2418   {\usebibmacro{prenote}%
2419   {}%
2420     \iffieldundef{shorthand}{no shorthand}%
2421       {\iffieldundef{labelyear}%
2422        {\usebibmacro{cite:label}%
2423         {\usebibmacro{cite:labelyear+extrayear}%
2424           \savefield{labelyear}{\cbx@lastyear}%
2425           {\iftoggle{cbx:shorthandintro}%
2426             {\ifciteseen{%
2427               {\usebibmacro{cite:shorthand}%
2428               {\iffieldundef{labelyear}%
2429                 {\usebibmacro{cite:label}%
2430                   {\usebibmacro{cite:labelyear+extrayear}%
2431                     \savefield{labelyear}{\cbx@lastyear}%
2432                     \usebibmacro{shorthandintro}%
2433                     \global\undef{\cbx@lastyear}%
2434                     {\usebibmacro{cite:shorthand}{}%
2435                       \savefield{namehash}{\cbx@lasthash}{}%
2436 \setunit{%
2437   \ifbool{cbx:parens}%
2438     {\bibcloseparen\global\boolfalse{cbx:parens}}%
2439   {}%
2440   \multicitedelim}{}%
2441
2442 \newbibmacro*[textcite:postnote:AY]{%
2443   \usebibmacro{postnote}%
2444   \ifthenelse{\value{multicitecount}=\value{multicitetotal}}
2445     {\setunit{}}%
2446     \printtext{%
2447       \ifbool{cbx:parens}%
2448         {\bibcloseparen\global\boolfalse{cbx:parens}}%
2449       {}}
2450     {\setunit{%
2451       \ifbool{cbx:parens}%
2452         {\bibcloseparen\global\boolfalse{cbx:parens}}%
2453       {}%
2454       \multicitedelim}}}
```

The `cite:shorthand` is the same for both author-title and author-year styles:

```

2455 \renewbibmacro*[cite:shorthand]{%
2456   \printtext[bibhyperref]{\printfield{shorthand}}}
```

If the field `entrysubtype` equals to `classic` the citation commands will use the author-title macros:

```

2457 \renewbibmacro*{cite:init}{%
2458   \switchclass{cite:init:AT}{cite:init:AY}}
2459 \renewbibmacro*{cite:reinit}{%
2460   \switchclass{cite:reinit:AT}{cite:reinit:AY}}
2461 \renewbibmacro*{cite}{%
2462   \switchclass{cite:AT}{cite:AY}}
2463 \renewbibmacro*{textcite}{%
2464   \switchclass{textcite:AT}{textcite:AY}}
2465 \renewbibmacro*{textcite:postnote}{%
2466   \switchclass{textcite:postnote:AT}{textcite:postnote:AY}}
2467
2468 \newbibmacro*{cite:noshorthand}{%
2469   \ifthenelse{\ifnameundef{labelname}\OR\iffieldundef{labelyear}}{%
2470     {\usebibmacro{cite:label}}%
2471     \setunit{\addspace}}%
2472 \usebibmacro{cite:labelyear+extrayear}%
2473   {\usebibmacro{cite:reinit}}%
2474   {\iffielddequals{namehash}{\cbx@lasthash}{%
2475     {\ifthenelse{\iffielddequals{labelyear}{\cbx@lastyear}\AND
2476       {(\value{multicitecount}=0\OR\iffieldundef{postnote})}}{%
2477       {\setunit{\addcomma}}%
2478       {\usebibmacro{cite:extrayear}}%
2479       {\setunit{\compcitedelim}}%
2480       {\usebibmacro{cite:labelyear+extrayear}}%
2481       {\savefield{labelyear}{\cbx@lastyear}}}}%
2482     {\printnames{labelname}}%
2483     \setunit{\nameyeardelim}}%
2484     {\usebibmacro{cite:labelyear+extrayear}}%
2485     {\savefield{namehash}{\cbx@lasthash}}%
2486     {\iffieldundef{postnote}}%
2487     {\savefield{labelyear}{\cbx@lastyear}}}}}}}
```

7.5.4 Citation commands

```

2488 \DeclareCiteCommand*{\cite}
2489   {\usebibmacro{cite:init}}%
2490   {\usebibmacro{prenote}}%
2491   {\usebibmacro{citeindex}}%
2492   {\switchclass{citetitle:AT}{citeyear}}%
2493   {}
2494   {\usebibmacro{postnote}}
2495
2496 \DeclareCiteCommand*{\parencite}[\mkbibparens]
2497   {\usebibmacro{cite:init}}%
2498   {\usebibmacro{prenote}}%
2499   {\usebibmacro{citeindex}}%
2500   {\switchclass{citetitle:AT}{citeyear}}%
2501   {}
2502   {\usebibmacro{postnote}}
2503
2504 \DeclareCiteCommand{\citetitle}
2505   {\boolfalse{citetracker}}%
```

```

2506  \boolfalse{pagetracker}%
2507  \usebibmacro{prenote}%
2508  {\indexfield{inextitle}%
2509    \printtext[bibhyperref]{\printfield[citetitle]{labeltitle}}}
2510  {\multicitedelim}
2511  {\usebibmacro{postnote}%
2512
2513 \DeclareCiteCommand{\citetitle}%
2514  {\boolfalse{citetracker}%
2515  \boolfalse{pagetracker}%
2516  \usebibmacro{prenote}%
2517  {\indexfield{inextitle}%
2518    \printtext[bibhyperref]{\printfield[citetitle]{title}}}
2519  {\multicitedelim}
2520  {\usebibmacro{postnote}%
2521
2522 \DeclareCiteCommand{\citeyear}%
2523  {\boolfalse{citetracker}%
2524  \boolfalse{pagetracker}%
2525  \usebibmacro{prenote}%
2526  {\printtext[bibhyperref]{\printfield{year}}}
2527  {\multicitedelim}
2528  {\usebibmacro{postnote}%
2529
2530 \DeclareCiteCommand{\footcitet}[\mkbibfootnote]%
2531  {\usebibmacro{cite:init}%
2532  {\usebibmacro{citeindex}%
2533    \usebibmacro{textcite}%
2534  {}%
2535  {\usebibmacro{textcite:postnote}}}
```

This command is now deprecated because it is substituted by the `entrysubtype=classic` mechanism:

```

2536 \DeclareCiteCommand{\sdcite}%
2537  {\boolfalse{citetracker}%
2538  \boolfalse{pagetracker}%
2539  \usebibmacro{prenote}%
2540  {\indexnames{labelname}%
2541    \printtext[bibhyperref]{\printnames{labelname}}%
2542    \setunit{\addcomma\space}%
2543    \indexfield{inextitle}%
2544    \printtext[bibhyperref]{\printfield[citetitle]{labeltitle}}}
2545  {\multicitedelim}
2546  {\usebibmacro{postnote}}}
```

7.6 philosophy-modern.cbx

The `modern` style uses the `classic` citation scheme:

```

2547 \RequireCitationStyle{philosophy-classic}
```

The `\fullcite` command simply prints the bibliography entry supplied by the style used. So we have to redefine this command in order to get the same output as that produced in the `philosophy-classic` style:

```

2548 \DeclareCiteCommand{\fullcite}%
2549   {\usebibmacro{prenote}%
2550   {\setkeys{blx@bib2}{restoreclassic}%
2551   \usedriver%
2552     {\DeclareNameAlias{sortname}{default}}%
2553     {\thefield{entrytype}}}}%
2554   {\multicitedelim}%
2555   {\usebibmacro{postnote}}%

```

7.7 philosophy-verbose.cbx

7.7.1 Initial settings

```

2556 \RequireCitationStyle{verbose-trad2}%
2557
2558 \newtoggle{cbx:sauthorscite}%
2559 \newtoggle{cbx:latinemph}%
2560 \newtoggle{cbx:commacit}%
2561
2562 \DeclareBibliographyOption{sauthorscite}[true]{%
2563   \settoggle{cbx:sauthorscite}{#1}%
2564 \DeclareBibliographyOption{latinemph}[true]{%
2565   \settoggle{cbx:latinemph}{#1}%
2566 \DeclareBibliographyOption{commacit}[true]{%
2567   \settoggle{cbx:commacit}{#1}%
2568
2569 \ExecuteBibliographyOptions{%
2570   idemtracker=false,
2571   loccittracker=strict,
2572   sauthorscite=false,
2573   latinemph=false,
2574   commacit=false}%
2575
2576 \AtEveryCite{%

```

The annotation field is omitted in every citations:

```
2577 \togglefalse{bbx:annotation}%
```

Redefine \mkibid for every citations when using the latinemph option:

```
2578 \iftoggle{cbx:latinemph}{\renewcommand*{\mkibid}{\emph}{}}%
```

Name formats

```

2579 \renewbibmacro*{name:andothers}{%
2580   \ifboolexpr{%
2581     test {\ifnumequal{\value{listcount}}{\value{liststop}}}%
2582     and
2583     test \ifmorenames
2584   }%
2585   {\ifnumgreater{\value{liststop}}{1}%
2586     {\finalandcomma}%
2587     {}%
2588     \andothersdelim\bibstring[\mkibid]{andothers}%
2589   }%
2590 \renewbibmacro*{list:andothers}{%

```

```

2591 \ifboolexpr{%
2592   test {\ifnumequal{\value{listcount}}{\value{liststop}}}{%
2593     and
2594     test \ifmoreitems
2595   }%
2596   {\ifnumgreater{\value{liststop}}{1}{%
2597     {\finalandcomma}%
2598   }{%
2599     \andmoredelim\bibstring[\mkbibid]{andmore}}%
2600   }%
2601 \iftoggle{cbx:scauthorscite}{%
2602 \DeclareNameFormat{labelname}{%
2603   \let\mkbibnamelast\mkbibsc%
2604   \let\mkbibnamefirst\mkbibsc%
2605   \let\mkbibnameprefix\mkbibsc%
2606   \let\mkbibnameaffix\mkbibsc
2607   \ifcase\value{uniquename}%
2608     \usebibmacro{name:last}{#1}{#3}{#5}{#7}%
2609   \or
2610     \ifuseprefix
2611       {\usebibmacro{name:first-last}{#1}{#4}{#5}{#8}}%
2612       {\usebibmacro{name:first-last}{#1}{#4}{#6}{#8}}%
2613   \or
2614     \usebibmacro{name:first-last}{#1}{#3}{#5}{#7}%
2615   \fi
2616   \usebibmacro{name:andothers}}{}%
2617 \DeclareNameFormat{scdefault}{%
2618   \let\mkbibnamelast\mkbibsc%
2619   \let\mkbibnamefirst\mkbibsc%
2620   \let\mkbibnameprefix\mkbibsc%
2621   \let\mkbibnameaffix\mkbibsc
2622   \iffirstinits
2623     {\usebibmacro{name:first-last}{#1}{#4}{#5}{#7}}%
2624     {\usebibmacro{name:first-last}{#1}{#3}{#5}{#7}}%
2625   \usebibmacro{name:andothers}}
2626 }
```

7.7.2 New macros

```

2627 \newbibmacro*[cite:opcit]{%
2628   \printtext[bibhyperlink]{\bibstring[\mkbibid]{opcit}}}
2629
2630 \newbibmacro*[cite:loccit]{%
2631   \printtext{%
2632     \bibhyperlink{cite\csuse{cbx@lastcite@\thefield{entrykey}}}{%
2633       \bibstring[\mkbibid]{loccit}}}}
2634 \global\toggletrue{cbx:loccit}
2635
2636 \renewbibmacro*[cite:ibid]{%
2637   \ifloccit
2638     {\usebibmacro{cite:loccit}}{%
2639       \printtext{%

```

```
2640     \bibhyperlink{cite\csuse{cbx@lastcite@\thefield{entrykey}}}{%
2641         \bibstring[\mkibid]{ibidem}}}}}}%  
2642  
2643 \renewbibmacro*{cite:title}{%OK  
2644     \ifsingletitle{\usebibmacro{cite:opcit}}{%
2645         \printtext[bibhyperlink]{%
2646             \printfield[citetitle]{labeltitle}}%  
2647             \iftoggle{cbx:commacit}{\setunit{\addcomma\space}}{%
2648                 \setunit{\addspace\midsentence}}}}%  
2649         \bibstring{cited}}}  
2650  
2651 % \renewbibmacro*{cite:full}{%OK  
2652 %     \usebibmacro{cite:full:citepages}}%  
2653 %     \global\toggletrue{cbx:fullcite}}%  
2654 %     \printtext[bibhypertarget]{%
2655 %         \usedriver  
2656 %             {\iftoggle{cbx:scauthorscite}{%
2657 %                 \Declarnamelistalias{sortname}{scdefault}}{%
2658 %                     {\Declarnamelistalias{sortname}{default}}}}}}%  
2659 %             {\thefield{entrytype}}}}%  
2660 %     \usebibmacro{shorthandintro}}}  
2661  
2662 \renewbibmacro*{cite:full}{%OK  
2663     \iftoggle{cbx:shorthandintro}{%
2664         \usebibmacro{cite:full:citepages}}%  
2665         \global\toggletrue{cbx:fullcite}}%  
2666         \printtext[bibhypertarget]{%
2667             \usedriver  
2668             {\iftoggle{cbx:scauthorscite}{%
2669                 \Declarnamelistalias{sortname}{scdefault}}{%
2670                     {\Declarnamelistalias{sortname}{default}}}}}}%  
2671             {\thefield{entrytype}}}}%  
2672     \usebibmacro{shorthandintro}}}%  
2673     {\usebibmacro{cite:shorthand}}}  
2674  
2675  
2676  
2677 \renewbibmacro*{cite:idem}{%
2678     \iftoggle{cbx:scauthorscite}{%
2679         \bibstring[\mkbibsc]{idem\thefield{gender}}}}{%
2680         \bibstring[\mkibid]{idem\thefield{gender}}}}%  
2681         \setunit{\nametitledelim}}}  
2682  
2683 \newbibmacro*{ccite:cite}{%
2684     \usebibmacro{related:clearauthors}}%  
2685     \usebibmacro{cite:citepages}}%  
2686     \global\togglefalse{cbx:fullcite}}%  
2687     \global\togglefalse{cbx:loccit}}%  
2688     \bibhypertarget{cite\the\value{instcount}}{%
2689         \ifciteseen  
2690             {\iffieldundef{shorthand}{%
2691                 {\usebibmacro{cite:title}}}}}}}
```

```

2692 \usebibmacro{cite:save}%
2693     {\usebibmacro{cite:shorthand}}%
2694     {\usebibmacro{cite:full}}%
2695     \usebibmacro{cite:save}}}}}
```

7.7.3 Citation commands

```

2696 \DeclareCiteCommand{\ccite}%
2697 {\usebibmacro{prenote}}%
2698 {\usebibmacro{citeindex}}%
2699 \usebibmacro{ccite:cite}}%
2700 {\multicitedelim}%
2701 {\usebibmacro{cite:postnote}}%
2702 \DeclareCiteCommand{\fullcite}%
2703 {\usebibmacro{prenote}}%
2704 {\usedriver
2705     {\iftoggle{cbx:sauthorscrite}{%
2706         {\DeclareNameAlias{sortname}{scdefault}}%
2707         {\DeclareNameAlias{sortname}{default}}}}%
2708     {\thefield{entrytype}}}%
2709 {\multicitedelim}%
2710 {\usebibmacro{postnote}}}
```

7.8 italian-philosophy.lbx

```

2711 \InheritBibliographyExtras{italian}%
2712
2713 \DeclareBibliographyExtras{%
2714 \protected\def\bibrangedash{%
2715     -\penalty\hyphenpenalty}%
2716 \protected\def\bibdatedash{\textendash}}%
2717
2718 \NewBibliographyString{origed,cited}%
2719
2720 \DeclareBibliographyStrings{%
2721     inherit      = {italian},%
2722     nodate       = {{senza data}{s\adddot{space d}\adddot}},%
2723     cited        = {{cit\adddot}{cit\adddot}},%
2724     opcit        = {{op\adddot{space cit\adddot}{op\adddot{space cit\adddot}}}},%
2725     ibidem       = {{ivi}{ivi}},%
2726     loccit       = {{ibidem}{ibidem}},%
2727     origed       = {{ed\adddot{space orig\adddot}{ed\adddot{space orig\adddot}}}},%
2728     langitalian = {{italiano}{it\adddot}},%
2729     editor        = {{\mkpureparens{a cura di}}{\mkpureparens{a cura di}}},%
2730     editors       = {{\mkpureparens{a cura di}}{\mkpureparens{a cura di}}},%
2731     backrefpage  = {{Citato a pagina}{Citato a \bibstring{page}\adddot}},%
2732     backrefpages = {{Citato alle pagine}{Citato alle \bibstring{pages}\adddot}},%
2733     pages         = {{pagine}{\iftoggle{bbx:classical}{pp\adddot}{p\adddot}}},%
2734     columns       = {{colonne}{\iftoggle{bbx:classical}{coll\adddot}{col\adddot}}},%
2735     lines         = {{righe}{\iftoggle{bbx:classical}{rr\adddot}{r\adddot}}},%
2736     verses        = {{versi}{\iftoggle{bbx:classical}{vv\adddot}{v\adddot}}},%
2737     section       = {{sezione}{sez\adddot}},%
2738     sections      = {{sezioni}{\iftoggle{bbx:classical}{sezz\adddot}{sez\adddot}}},%
2739     paragraphs    = {{paragrafi}{\iftoggle{bbx:classical}{parr\adddot}{par\adddot}}},%
```

```

2740 volumes      = {{volumi}\iftoggle{bbx:classical}{voll\adddot}{vol\adddot}}},
2741 withcommentator = {{con commenti di}{con comm\adddot\addabbrvspace di}},
2742 withannotator   = {{annotazioni di}{annotazioni di}},
2743 withintroduction = {{introduzione di}{introduzione di}},
2744 withforeword     = {{prefazione di}{prefazione di}},
2745 withafterword    = {{postfazione di}{postfazione di}},
2746 reprintas       = {{ristampato}{rist\adddot}},
2747 % reprintfrom   = {{}}{}, % FIXME: missing
2748 translationof   = {{traduzione di}{trad\adddotspace di}},
2749 translationas   = {{traduzione italiana}{trad\adddotspace it\adddot}},
2750 % translationfrom = {{}}{}, % FIXME: missing
2751 reviewof        = {{Recensione di}{Recensione di}},
2752 % origpubas     = {{}}{}, % FIXME: missing
2753 % origpubin     = {{}}{}, % FIXME: missing
2754 % astitle       = {{}}{}, % FIXME: missing
2755 % bypublisher   = {{}}{}, % FIXME: missing
2756 byreviser      = {{revisione di}{revisione di}}
2757 }

```

7.9 english-philosophy.lbx

```

2758 \InheritBibliographyExtras{english}
2759
2760 \DeclareBibliographyExtras{%
2761 \protected\def\bibrangedash{%
2762   -\penalty\hyphenpenalty}%
2763 \protected\def\bibdatedash{\textendash}}%
2764
2765 \NewBibliographyString{cited,origed}
2766
2767 \DeclareBibliographyStrings{%
2768 inherit      = {english},
2769 nodate       = {{no date}{n\adddot d\adddot}},
2770 cited        = {{cit\adddot}{cit\adddot}},
2771 ibidem       = {{ivi}{ivi}},
2772 loccit       = {{ibidem}{ibidem}},
2773 origed       = {{orig\adddotspace ed\adddot}{orig\adddotspace ed\adddot}},
2774 editor        = {{\mkpureparens{ed\adddot}}{\mkpureparens{ed\adddot}}},
2775 editors       = {{\mkpureparens{eds\adddot}}{\mkpureparens{eds\adddot}}},
2776 reviewof      = {{Review of}{Review of}},
2777 translationas = {{trans\adddot}{trans\adddot}},
2778 backrefpage   = {{cited on page}{cited on p\adddot}},
2779 backrefpages  = {{cited on pages}{cited on pp\adddot}}
2780 }

```

7.10 spanish-philosophy.lbx

Thanks to Eduardo Villegas for these translations.

```

2781 %
2782 %--A Thanks to Eduardo Villegas for these translations.
2783 %
2784 \InheritBibliographyExtras{spanish}
2785

```

```

2786 \DeclareBibliographyExtras{%
2787   \protected\def\bibrangedash{%
2788     -\penalty\hyphenpenalty}%
2789   \protected\def\bibdatedash{\textendash}}%
2790
2791 \NewBibliographyString{origed,cited}
2792
2793 \DeclareBibliographyStrings{%
2794   inherit      = {spanish},
2795   cited        = {{cit\adddot}{cit\adddot}},
2796   opcit        = {{op\adddot cit\adddot}{op\adddot cit\adddot}},
2797   ibidem       = {{ivi}{ivi}},
2798   loccit       = {{ibidem}{ibidem}},
2799   origed       = {{edici\'{o}n original}{ed\adddot orig\adddot}},
2800   langspanish  = {{espa\~nol}{es\adddot}},
2801   editor        = {{\mkpureparens{ed\adddot}}{\mkpureparens{ed\adddot}}},
2802   editors       = {{\mkpureparens{ed\adddot}}{\mkpureparens{eds\adddot}}},
2803   backrefpage  = {{Citado en la p\'agina}
2804   {Citado en la \bibstring{page}\adddot}}, %%FIXME: Maiuscola iniziale?
2805   backrefpages  = {{Citado en las p\'aginas}
2806   {Citado en las \bibstring{pages}\adddot}}, %%FIXME: Maiuscola iniziale?
2807   pages         = {{p\'aginas}{\iftoggle{bbx:classical}
2808   {p\'ags\adddot}{p\'ag\adddot}}},
2809   columns       = {{columnas}{\iftoggle{bbx:classical}{cols\adddot}{col\adddot}}},
2810   lines         = {{l\'ineas}{\iftoggle{bbx:classical}{ll\adddot}{l\adddot}}},
2811   verses        = {{versos}{\iftoggle{bbx:classical}{vv\adddot}{v\adddot}}},
2812   volumes       = {{vol\'umes}}
2813   {\iftoggle{bbx:classical}{vols\adddot}{vol\adddot}},
2814   withcommentator = {{comentarios de}{com\adddot\addabrvspace de}},
2815   withannotator  = {{notas de}{notas de}},
2816   withintroduction = {{introducci\'{o}n de}{intr\addotspace de}},
2817   withforeword    = {{prefacio de}{pref\addotspace de}},
2818   withafterword   = {{postfacio de}{postfacio de}},
2819   reprintas      = {{reimpresi\'{o}n}{reimp\adddot}},
2820   translationof  = {{traducci\'{o}n}{trad\addotspace de}},
2821   translationas  = {{traducido}{trad\addotspace es\adddot}},
2822   reviewof       = {{Rese\~na}{Rese\~na}}, %%FIXME: Maiuscola iniziale?
2823   section        = {{secci\'{o}n}{sec\adddot}},
2824   sections       = {{secciones}{\iftoggle{bbx:classical}
2825   {secs\adddot}{sec\adddot}}},
2826   byreviser     = {{revisi\'{o}n}{rev\addotspace de}}}
2827 }

```

Change History

v0.4

General: Improved compatibility for
 biblatex version 0.9 1

v0.5

General: Added new bibliography style

philosophy-verbose. Added localization file `italian-philosophy.lbx`.
 Added package options `origparens`,
`origbrackets`, `latinemph`. Changed
 package options `scauthors`,

	scauthorscite, scauthorsbib. Renamed file <code>biblatex-philosophy-doc.tex</code> to <code>philosophy-authoryear-doc.tex</code> . Added file <code>philosophy-verbose-doc.tex</code> . Updated documentation	1	vo.8c	General: Removed <code>biber.conf</code> configuration file. Added internal <code>biber</code> settings with <code>\DeclareDriverSourcemap</code> command. Added <code>trans-</code> field alias	1
vo.6	General: Added localization file <code>italian-philosophy.lbx</code> . Added file <code>philosophy-standard.bbx</code> . New documentation file <code>biblatex-philosophy</code> . Removed files <code>philosophy-authoryear-doc.tex</code> , <code>philosophy-verbose-doc.tex</code>	1	vo.8d	General: Fixed some bugs related to <code>\DeclareDriverSourcemap</code> , <code>\ccite</code> , and <code>@review</code> entry type	1
vo.7	General: Removed package option <code>colonloc</code> . Removed package options <code>origparens</code> <code>origbrackets</code> . Added package options <code>origfieldsformat</code> , <code>publocformat</code> , <code>commacit</code> , <code>inbeforejournal</code> , <code>romanvol</code> , <code>volnumformat</code> . Added command <code>volnumpunct</code> . Added citation commands <code>\sdcite</code> , <code>\ccite</code> . Updated documentation	1	vo.8e	General: Improved <code>relatedformat</code> option for cascading entries. Implemented cross-referencing mechanism for <code>@inproceedings</code> entries. Improved <code>\ccite</code> command. Changed the values for the <code>entrysubtype</code> from <code>classical</code> to <code>classic</code> . Added <code>nodate</code> package option.	1
vo.7a	General: Added command <code>volumfont</code> . Added command <code>footcitet</code> . Updated documentation	1	vo.8f	General: New option <code>nodate</code> for <code>\printbibliography</code> command	1
vo.7b	General: Removed package option <code>romanvol</code> . Added package option <code>volumeformat</code> . Added package option <code>editionformat</code> . Activated the option <code>singletitle</code> for style <code>philosophy-verbose</code> . Added bibliography driver <code>@review</code> . Added bibliography string <code>cit</code> . Added bibliography string <code>reviewof</code> . Updated documentation	1	vo.9a	General: Maintenance release. Corrected some bugs.	1
vo.7c	General: Fixed some bugs. New <code>origfieldtype</code> option. Added <code>nodate</code> bibliography string. Updated documentation	1	vo.9b	General: Updated bibliography drivers to correct a bug when using the <code>related</code> mechanism.	1
vo.8a	General: New <code>entrysubtype</code> field for citing classical texts. New <code>related</code> field mechanism. New <code>relatedformat</code> option. New English documentation. Fixed some bugs	1	vo.9c	General: Maintenance release. Corrected some bugs.	1
vo.8b	General: Added <code>biber.conf</code> configuration file	1	vo.9d	General: Maintenance release. Corrected some bugs.	1
			vo.9e	General: Maintenance release. Updated documentation.	1
			vo.9f	General: Updated documentation. Corrected a bug in the <code>volnumformat</code> option.	1
			vo.9g	General: Added localization module for spanish. Corrected a bug in <code>@inbook</code> and <code>@incollection</code> entries when using <code>crossref</code> field. Updated documentation.	1
			vo.9h	General: New option <code>lowscauthors</code> . Corrected some bugs. Updated documentation.	1

vo.9i		related format options: now the related block is not preceded by semi-colon when using values parens and brackets styles. Updated documentation	1
General: Corrected a bug with shorthandintro option.	1		
v1.0			
General: Corrected a bug in volumeformat and volnumformat options. Change value romanupp to Roman in volume format and edition format. Corrected bug in		v1.1	
		General: Maintenance release. Updated documentation.	1

Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols

\`	2799, 2803, 2805, 2807, 2808, 2810, 2812, 2816, 2819, 2820, 2823, 2826
\((.	2370, 2381, 2476
\)	2370, 2381, 2476
\~	2800, 2820–2822
A	
\addabrvspace .	2741, 2814
\addcolon . . .	246, 408, 426, 551, 560, 569, 1399
\addcomma .	111, 114, 234, 248, 258, 260, 268, 282, 315, 319, 422, 438, 461, 467, 524, 533, 542, 578, 587, 596, 604, 624, 1487, 1495, 1498, 1618, 1623, 1727, 1854, 1883, 1958, 2028, 2061, 2198, 2200, 2215, 2217, 2371, 2382, 2477, 2542, 2647
\adddot	510, 2722–2724, 2727, 2728, 2731–2741, 2746, 2749, 2769, 2770, 2773–2775, 2777–2779, 2795, 2796, 2799–2802, 2804, 2806, 2808– 2811, 2813, 2814, 2819, 2821, 2823, 2825

\adddotspace	1472, 1482, 2722, 2724, 2727, 2748, 2749, 2773, 2816, 2817, 2820, 2821, 2826
\addperiod	112, 499, 505, 516
\addsemicolon	309, 338, 635, 636, 669, 720, 760, 809, 874, 937, 1002, 1052, 1090, 1130, 1171, 1203, 1254, 1298, 1338, 1372, 1560, 2136, 2184
\addspace	113, 145, 146, 231, 236, 244, 256, 326, 399, 403, 406, 414, 419, 424, 446, 458, 550, 559, 568, 577, 586, 595, 601, 622, 1151, 1155, 1275, 1483, 1491, 1493, 1620, 1634, 1648, 1693, 1696, 1723, 1726, 1731, 1734, 1750, 1754, 1757, 1767, 1780, 1850, 1859, 1892, 1905, 1954, 1957, 1962, 1965, 1980, 1984, 1987, 2026, 2046, 2059, 2074, 2201, 2213, 2218, 2300, 2325, 2395, 2406, 2416, 2471, 2648
\AND	2369, 2380, 2475
\andmoredelim	2599
\andothersdelim	2588
\annotationfont	130, 156
\AtBeginBibliography	92, 1805
\AtBeginDocument	84, 1669
\AtBeginShorthands	1616, 1813, 1999
\AtEveryBibitem	1678
\AtEveryCite	2236, 2576
B	
\bbx@crossref@inbook	833, 836, 1625, 1759, 1884, 2001, 2192
\bbx@crossref@incollection	898, 901, 961, 964, 1639, 1772, 1897, 2008, 2207
\bbx@editionformat	39, 53, 133, 135, 202, 204, 206, 208
\bbx@lasthash	1732, 1755, 1857, 1877, 1963, 1985, 2031, 2050, 2063, 2077
\bbx@origfields	38, 51, 58, 274, 345, 355, 1508
\bbx@publocformat	35, 43, 220, 222, 472, 474, 476, 480, 482, 484, 488, 490, 492
\bbx@relatedformat	37, 47, 49, 213, 215,

\bbx@volnumformat	217, 305, 307, 332, 335, 669, 719, 759, 808, 873, 936, 1001, 1051, 1089, 1129, 1170, 1202, 1253, 1297, 1337, 1371, 1559, 2135, 2183	2448, 2452, 2505, 2506, 2514, 2515, 2523, 2524, 2537, 2538	1639, 1759, 1772, 1884, 1897, 2001, 2008, 2192, 2207, 2488, 2496, 2504, 2513, 2522, 2530, 2536, 2548, 2696, 2702
\bbx@volumeformat	40, 55, 170, 172, 174, 176, 184, 186, 188, 190	C	\DeclareDataInheritance 1590
\bibclosebracket	1672	\cbx@lasthash	\DeclareEntryOption 57
\bibcloseparen	1672, 2314, 2332, 2336, 2438, 2448, 2452	\cbx@lastyear	\DeclareFieldAlias 1592–1594
\bibrpsstring	1467	2343, 2345, 2474, 2485	\DeclareFieldFormat 144–159, 167, 179, 193, 196, 200, 212, 1461, 1462, 1464– 1466, 1468, 1470, 1472
\bibdatedash	2716, 2763, 2789	2347, 2351, 2369, 2375, 2380, 2386, 2389, 2424, 2431, 2433, 2475, 2481, 2487	\DeclareLanguageMapping 3–5
\bibhang	1803, 1810, 1820, 1928	\ccite 2696	\DeclareNameAlias 619, 1474, 2203, 2220, 2552, 2657, 2658, 2669, 2670, 2706, 2707
\bibhyperlink	2632, 2640	\cite 2488	\DeclareNameFormat 94, 2243, 2602, 2618
\bibhyperref	2244	\citetitle 2504, 2513	\DeclareStyleSourcemap 1570
\bibhypertarget	2688	\citeyear 2522	
\bibitemsep	1801	\ClassError 162	
\bibnamedash	1719, 1748, 1950, 1978, 2023, 2044	\clearfield 1655, 1656, 1701, 1702, 1818, 1819, 1835, 1912, 1913, 1932, 1933, 1993	
\bibnamesep	1802	\clearname 1753, 1882, 1983, 2049, 2076	
\bibopenbracket	1671	\compitedelim	
\bibopenparen	1671, 2300, 2325, 2395, 2406, 2416	2275, 2294, 2373, 2376, 2384, 2479	
\bibpagerefpunct	1431, 1453	\csuse 2632, 2640	
\bibpagespunct	221, 223, 225		
\bibrangedash	2714, 2761, 2787		
\bibsstring	1465	D	E
\bibstring	145, 146, 168, 181, 195, 198, 199, 203, 205, 207, 209, 275– 277, 508, 509, 633, 634, 1663, 1709, 1827, 1920, 1940, 2202, 2219, 2588, 2599, 2628, 2633, 2641, 2649, 2679, 2680, 2731, 2732, 2804, 2806	\DeclareBibliographyDriver 638, 678, 729, 769, 818, 883, 946, 1011, 1061, 1099, 1139, 1180, 1212, 1263, 1307, 1347, 1381, 1514	\edfnt 139
\blx@blxinit	117	\DeclareBibliographyExtras 2713, 2760, 2786	\editionfont 132, 141
\blx@postpunct	119	\DeclareBibliographyOption 16, 18,	\emph 1471, 2578
\blx@setsfcodes	118	20, 22, 24, 26, 28, 31, 42, 44, 46, 48, 50, 52, 54, 1602, 1604, 1793, 2228, 2562, 2564, 2566	\ExecuteBibliographyOptions 60, 1463, 1607, 1795, 2231, 2569
\boolfalse	2263, 2314, 2332, 2336, 2341, 2438,	\DeclareBibliographyStrings 2720, 2767, 2793	F
		\DeclareCiteCommand 616, 1625,	\finalandcomma 2586, 2597
			\finentry 515, 517, 518
			\footcitet 2530
			\footnotesize 130
			\fullcite 2548, 2702
			G
			\global 1732, 1755, 1857, 1877, 1963, 1985, 2031, 2050, 2063, 2077, 2263, 2264, 2267, 2270, 2299, 2314, 2324, 2332, 2336, 2341–2343, 2346, 2347, 2350, 2351,

- 2389, 2394, 2405,
2415, 2433, 2438,
2448, 2452, 2634,
2653, 2665, 2686, 2687
- Guzmán de Rojas,
Iván@Guzmán de
Rojas, Iván 9
- H**
- \hskip 1810, 1829
- \hyphenpenalty
. 2715, 2762, 2788
- I**
- \ifbibindex 124
- \ifbibstring 199
- \ifblank 103
- \ifblx@load@version@one
. 1568
- \ifbool 2313, 2331,
2335, 2437, 2447, 2451
- \ifboolexpr 295,
452, 1475, 1657,
1685, 1703, 1713,
1742, 1821, 1840,
1867, 1914, 1934,
1944, 1972, 2017,
2038, 2052, 2068,
2080, 2086, 2580, 2591
- \ifciteindex 122
- \ifcitereen 2194,
2209, 2308, 2358,
2378, 2401, 2426, 2689
- \ifdefstring 133,
135, 170, 172, 174,
176, 180, 184, 186,
188, 190, 194, 202,
204, 206, 208, 213,
215, 217, 220, 222,
274, 305, 307, 332,
335, 345, 355, 431,
433, 435, 472, 474,
476, 480, 482, 484,
488, 490, 492, 669,
719, 759, 808, 873,
936, 1001, 1051,
1089, 1129, 1170,
1202, 1253, 1297,
1337, 1371, 1508,
1559, 1691, 2135, 2183
- \iffieldequals
. 2274, 2293, 2367,
2369, 2380, 2474, 2475
- \iffieldequalstr 1471,
1481, 1490, 1679, 2258
- \iffieldsequal 266
- \iffieldundef 265, 269,
273, 280, 283, 288,
296, 298, 300, 302,
313, 316, 320, 374,
376, 380, 389, 400,
415, 443, 453, 455,
497, 514, 632, 701,
782, 831, 832, 857,
896, 897, 920, 959,
960, 985, 1225, 1395,
1409, 1441, 1469,
1485, 1496, 1526,
1537, 1627, 1641, 1658,
1660, 1686, 1688,
1704, 1706, 1722,
1725, 1728, 1822,
1824, 1833, 1834,
1849, 1852, 1880,
1915, 1917, 1935, 1937,
1953, 1956, 1959,
1990, 1991, 2003,
2010, 2025, 2058,
2117, 2157, 2265,
2273, 2287, 2305,
2344, 2354, 2368,
2370, 2381, 2391,
2420, 2421, 2428,
2469, 2476, 2486, 2690
- \iffirstinits 100, 106, 2623
- \ifinteger
169, 183, 197, 201, 1467
- \iflistundef
. 229, 241, 243, 253,
255, 331, 503, 521,
530, 539, 549, 558,
567, 576, 585, 594, 1153
- \ifloccit 2637
- \ifmoreitems 2594
- \ifmorenames 2583
- \ifnamesequal 1390
- \ifnameundef 1478, 1716,
1745, 1843, 1870,
1947, 1975, 2020,
2041, 2055, 2071,
2083, 2089, 2276,
2295, 2322, 2390, 2469
- \ifnumequal
. 99, 2302, 2396,
2407, 2417, 2581, 2592
- \ifnumgreater 507, 2585, 2596
- \ifnumless 2262, 2340
- \ifsingletitle 2644
- \ifstrequal 1788, 1927
- \ifthenelse 1630,
1644, 1763, 1776,
1888, 1901, 2195,
2210, 2328, 2369,
2380, 2444, 2469, 2475
- \iftoggle 85,
88, 93, 496, 513, 653,
660, 668, 710, 718,
758, 799, 807, 864,
872, 927, 935, 992,
1000, 1042, 1050,
1088, 1120, 1128,
1169, 1193, 1201, 1244,
1252, 1288, 1296,
1328, 1336, 1364,
1370, 1424, 1432,
1448, 1454, 1550,
1558, 1662, 1670,
1708, 1806, 1826,
1919, 1939, 2126,
2134, 2174, 2182,
2200, 2217, 2237,
2307, 2356, 2377,
2400, 2425, 2578,
2601, 2647, 2656,
2663, 2668, 2678,
2705, 2733–2736,
2738–2740, 2807,
2809–2811, 2813, 2824
- \ifuseauthor
. 1476, 1714, 1841,
1945, 2018, 2053, 2081
- \ifuseeditor 1629, 1643,
1743, 1762, 1775,
1868, 1887, 1900,
1973, 2039, 2069, 2087
- \ifuseprefix 2248, 2610
- \ignorespaces 1810
- \indexfield 2508, 2517, 2543
- \indexnames
. 122, 124–128, 2540
- \InheritBibliographyExtras
. 2711, 2758, 2784
- \intitlepunct 113
- \isdot 211
- L**
- L’arte di scrivere con

- L*A_TE_X@*L’arte di scrivere con L*A_TE_X . . . 4
- \labelnamepunct 614, 642, 682, 733, 773, 823, 888, 951, 1015, 1065, 1103, 1143, 1184, 1216, 1267, 1311, 1351, 1518, 1618, 1811, 1815, 1929, 2098, 2148
- \libraryfont 131, 157
- M**
- \MakeLowercase 86
- \map 1572
- \maps 1571
- \midsentence . . . 119, 384, 393, 403, 419, 1663, 1709, 1827, 1920, 1940, 2201, 2218, 2648
- \mkbibbrackets . . . 216, 636
- \mkbibemph 144, 148, 149, 151, 152
- \mkbibfootnote 2530
- \mkbibnameaffix 98, 2241, 2606, 2622
- \mkbibnamefirst 96, 2239, 2604, 2620
- \mkbibnamelast 95, 2238, 2603, 2619
- \mkbibnameprefix 97, 2240, 2605, 2621
- \mkbibordedition 203
- \mkbibordseries 198
- \mkbibparens 2496
- \mkbibquote 147, 150, 153
- \mkbibsc 86, 87, 95–98, 2238–2241, 2603– 2606, 2619–2622, 2679
- \mkibid 2578, 2588, 2599, 2628, 2633, 2641, 2680
- \mkpageprefix 154, 1469
- \mkpureparens 115, 158, 159, 214, 635, 2729, 2730, 2774, 2775, 2801, 2802
- \multicitedelim 2284, 2290, 2316, 2338, 2364, 2440, 2454, 2510, 2519, 2527, 2545, 2554, 2700, 2709
- N**
- \nametitledelim 2279, 2681
- \nameyeardelim 2483
- \NewBibliographyString 2718, 2765, 2791
- \newbibmacro 219, 228, 240, 252, 264, 272, 279, 286, 294, 312, 324, 330, 351, 361, 366, 373, 495, 520, 529, 538, 547, 556, 565, 574, 583, 592, 600, 603, 606, 840, 905, 968, 1394, 1402, 1440, 1473, 1502, 1653, 1666, 1910, 2051, 2065, 2067, 2079, 2094, 2144, 2261, 2269, 2272, 2286, 2292, 2318, 2321, 2339, 2349, 2353, 2366, 2442, 2468, 2627, 2630, 2683
- \newblock 291, 343, 346, 348, 353, 356, 358, 642, 646, 648, 650, 652, 655, 657, 659, 663, 665, 667, 674, 682, 686, 688, 690, 694, 696, 698, 705, 709, 713, 715, 717, 725, 733, 737, 739, 741, 743, 745, 747, 749, 753, 755, 757, 765, 773, 777, 779, 788, 790, 792, 794, 798, 802, 804, 806, 814, 823, 827, 829, 834, 837, 842, 844, 846, 850, 852, 854, 861, 863, 867, 869, 871, 879, 888, 892, 894, 899, 902, 907, 909, 913, 915, 917, 924, 926, 930, 932, 934, 942, 951, 955, 957, 962, 965, 970, 972, 976, 978, 980, 989, 991, 995, 997, 999, 1007, 1015, 1019, 1021, 1023, 1025, 1027, 1033, 1037, 1041, 1045, 1047, 1049, 1057,
- 1065, 1069, 1071, 1073, 1075, 1081, 1083, 1085, 1087, 1095, 1103, 1107, 1109, 1111, 1115, 1117, 1119, 1123, 1125, 1127, 1135, 1143, 1147, 1149, 1158, 1160, 1162, 1164, 1166, 1168, 1176, 1184, 1188, 1190, 1192, 1196, 1198, 1200, 1208, 1216, 1220, 1222, 1224, 1231, 1233, 1235, 1239, 1243, 1247, 1249, 1251, 1259, 1267, 1271, 1273, 1277, 1281, 1283, 1287, 1291, 1293, 1295, 1303, 1311, 1315, 1317, 1319, 1323, 1327, 1331, 1333, 1335, 1343, 1351, 1355, 1357, 1359, 1361, 1363, 1367, 1369, 1377, 1404, 1406, 1415, 1417, 1419, 1421, 1423, 1427, 1429, 1431, 1436, 1445, 1447, 1451, 1453, 1458, 1504, 1506, 1509, 1511, 1518, 1520, 1523, 1525, 1529, 1534, 1543, 1545, 1547, 1549, 1553, 1555, 1557, 1565, 2098, 2102, 2104, 2106, 2110, 2112, 2114, 2121, 2125, 2129, 2131, 2133, 2141, 2148, 2152, 2154, 2163, 2165, 2167, 2169, 2173, 2177, 2179, 2181, 2189
- \newcounter 82, 83
- \newlength 1797, 1798
- \newrobustcmd 86, 87, 115, 139
- \newtoggle 6–12, 14, 1599, 1600, 1792, 2226, 2558–2560
- \newunit 238, 250, 262, 291, 322, 343, 346, 348, 353, 356, 358, 402, 404, 410, 417, 420, 428, 448, 463, 469,

527, 536, 545, 554,	1291, 1293, 1303,	\printdateextra
563, 572, 581, 590,	1313, 1315, 1317, 1319,	. 1664, 1710, 1828, 1941
599, 644, 646, 648,	1321, 1323, 1325, 1327,	\printeventdate 462, 1500
650, 652, 655, 657,	1331, 1333, 1343, 1353,	\printfield 222,
659, 663, 665, 674,	1355, 1357, 1359, 1361,	224, 226, 267, 270,
684, 686, 688, 690,	1363, 1367, 1377,	281, 284, 314, 318,
692, 694, 696, 698,	1404, 1406, 1408,	321, 342, 344, 352,
700, 705, 707, 709,	1413, 1415, 1417, 1419,	354, 362, 364, 369,
713, 715, 725, 735,	1421, 1423, 1427,	371, 375, 377, 383,
737, 739, 741, 743,	1429, 1436, 1445,	386, 392, 395, 403,
745, 747, 749, 751,	1447, 1451, 1458,	418, 423, 439, 445,
753, 755, 765, 775,	1504, 1506, 1509,	451, 460, 466, 468,
777, 779, 781, 786,	1511, 1520, 1523, 1525,	500, 517, 651, 661,
788, 790, 792, 794,	1529, 1534, 1536,	691, 693, 697, 702,
796, 798, 802, 804,	1541, 1543, 1545,	703, 708, 711, 742,
814, 825, 827, 829,	1547, 1549, 1553,	744, 746, 752, 780,
834, 837, 842, 844,	1555, 1565, 1698,	783, 784, 787, 791,
846, 848, 850, 852,	2100, 2102, 2104,	797, 800, 847, 849,
854, 856, 861, 863,	2106, 2108, 2110,	853, 858, 859, 865,
867, 869, 879, 890,	2112, 2114, 2116, 2121,	910, 912, 916, 921,
892, 894, 899, 902,	2123, 2125, 2129,	922, 928, 975, 979,
907, 909, 911, 913,	2131, 2141, 2150,	986, 987, 993, 1024,
915, 917, 919, 924,	2152, 2154, 2156,	1028, 1030, 1032,
926, 930, 932, 942,	2161, 2163, 2165,	1040, 1043, 1074,
953, 955, 957, 962,	2167, 2169, 2171,	1076, 1078, 1080,
965, 970, 972, 974,	2173, 2177, 2179, 2189	1112, 1114, 1150, 1152,
976, 978, 980, 982,	\newunitpunct 111, 1815, 1929	1161, 1191, 1194, 1226,
984, 989, 991, 995,	\nobreak 516, 1809	1227, 1230, 1234,
997, 1007, 1017, 1019,	\noinherit 1590	1242, 1245, 1274,
1021, 1023, 1025,	\nopunct 113, 276, 277, 306,	1276, 1278, 1280,
1027, 1029, 1031,	308, 333, 336, 367, 510	1286, 1289, 1318,
1033, 1035, 1037,		1320, 1326, 1329,
1039, 1041, 1045,		1358, 1360, 1397,
1047, 1057, 1067,		1398, 1400, 1407,
1069, 1071, 1073,		1410, 1411, 1414, 1418,
1075, 1077, 1079,		1425, 1442, 1443,
1081, 1083, 1085,		1449, 1497, 1503,
1095, 1105, 1107,		1505, 1507, 1531,
1109, 1111, 1113, 1115,		1532, 1535, 1538, 1539,
1117, 1119, 1123, 1125,		1542, 1544, 1551, 1693,
1135, 1145, 1147, 1149,		1696, 1724, 1835–
1158, 1160, 1162, 1164,		1837, 1851, 1922,
1166, 1176, 1186, 1188,		1923, 1955, 1992,
1190, 1192, 1196, 1198,		1994, 1995, 2027,
1208, 1218, 1220,		2060, 2107, 2109,
1222, 1224, 1229,		2113, 2118, 2119,
1231, 1233, 1235, 1237,		2124, 2127, 2155,
1239, 1241, 1243,		2158, 2159, 2162,
1247, 1249, 1259,		2166, 2172, 2175,
1269, 1271, 1273,		2199, 2216, 2319,
1277, 1279, 1281,		2327, 2456, 2509,
1283, 1285, 1287,		2518, 2526, 2544, 2646

\printlist	230, 233, 235, 242, 247, 254, 259, 510, 523, 525, 532, 534, 541, 543, 548, 552, 557, 561, 566, 570, 575, 579, 584, 588, 593, 597, 645, 685, 736, 776, 826, 891, 954, 981, 1018, 1034, 1068, 1106, 1116, 1146, 1157, 1187, 1219, 1236, 1270, 1314, 1354, 1522, 2101, 2151	Aymara	9	370, 375, 385, 394, 399, 403, 406, 408, 414, 419, 422, 424, 426, 438, 446, 458, 461, 467, 499, 505, 516, 524, 533, 542, 550, 551, 559, 560, 568, 569, 577, 578, 586, 587, 595, 596, 601, 604, 622, 624, 634, 642, 669, 670, 682, 720, 721, 733, 760, 761, 773, 809, 810, 823, 874, 875, 888, 937, 938, 951, 1002, 1003, 1015, 1052, 1053, 1065, 1090, 1091, 1103, 1130, 1131, 1143, 1151, 1155, 1171, 1172, 1184, 1203, 1204, 1216, 1254, 1255, 1267, 1275, 1298, 1299, 1311, 1338, 1339, 1351, 1372, 1373, 1399, 1431, 1453,
\printnames .	1392, 1484, 1631, 1632, 1645, 1646, 1721, 1749, 1764, 1765, 1777, 1778, 1848, 1874, 1889, 1890, 1902, 1903, 1952, 1979, 2024, 2045, 2057, 2073, 2196, 2197, 2211, 2212, 2278, 2297, 2413, 2482, 2541	\protect	1382	
\printorigdate .	232, 237, 245, 249, 257, 261	\protected .	2714, 2716, 2761, 2763, 2787, 2789	
\printtext .	274, 277, 306, 308, 310, 333, 336, 339, 368, 382, 391, 442, 459, 506, 517, 1156, 1482, 1492, 1497, 1530, 1662, 1664, 1692, 1695, 1708, 1710, 1724, 1820, 1826, 1828, 1837, 1851, 1883, 1919, 1921, 1939, 1941, 1955, 2027, 2060, 2198, 2215, 2319, 2330, 2446, 2456, 2509, 2518, 2526, 2541, 2544, 2628, 2631, 2639, 2645, 2654, 2666	R		
Problemática	lógica- lingüística de la co- municación social con el pueblo Ay- mara@Problemática <i>logico-lingüística de</i> <i>la comunicación so-</i> <i>cial con el pueblo</i>	\relatedcite	616, 637	
		\renewbibmacro .	121, 123, 341, 379, 388, 397, 412, 430, 441, 450, 465, 471, 479, 487, 502, 512, 607–613, 621, 623, 629, 1389, 1619, 1622, 1682– 1684, 1699, 1712, 1737, 1739, 1741, 1816, 1832, 1839, 1862, 1864, 1866, 1930, 1943, 1967, 1969, 1971, 1989, 2016, 2033, 2035, 2037, 2455, 2457, 2459, 2461, 2463, 2465, 2579, 2590, 2636, 2643, 2651, 2662, 2677	
		\RequireBiber	1	
		\RequireBibliographyStyle	2, 1596, 1597, 1791, 1997, 1998	
		\RequireCitationStyle	2224, 2547, 2556	
		\RN . .	173, 187, 205, 1464, 1467	
		\Rn . .	175, 177, 189, 191, 207, 209	
		\romannumeral	142	
		S		
		\savefield 2280, 2301, 2375, 2386, 2424, 2431, 2435, 2481, 2485, 2487	
		\sdcite	2536	
		\setlength 1799–1803, 1807, 1928	
		\settoggle	17, 19, 21, 23, 25, 27, 29, 32, 1603, 1605, 1794, 2229, 2563, 2565, 2567	
		\setunit	221, 223, 225, 231, 234, 236, 244, 246, 248, 256, 258, 260, 268, 282, 309, 315, 319, 326, 338, 363,	
				2275, 2279, 2284, 2290, 2294, 2298, 2312, 2323, 2326, 2329, 2334, 2364, 2371, 2373, 2376, 2382, 2384, 2393, 2404, 2414, 2436, 2445, 2450, 2471,

2477, 2479, 2483,	544, 553, 562, 571,	1250, 1256, 1257,
2542, 2647, 2648, 2681	580, 589, 598, 607–	1260, 1261, 1264–
\step 1573–1585	613, 620, 639–641,	1266, 1268, 1272,
\subtitlepunct 112, 385, 394	643, 647, 649, 653,	1282, 1284, 1292,
\switchclass 2257,	654, 656, 658, 664,	1294, 1300, 1301,
2458, 2460, 2462,	666, 671, 672, 675,	1304, 1305, 1308–
2464, 2466, 2492, 2500	676, 679–681, 683,	1310, 1312, 1316, 1322,
	687, 689, 695, 699,	1324, 1332, 1334,
T	706, 714, 716, 722,	1340, 1341, 1344,
\textendash 2716, 2763, 2789	723, 726, 727, 730–	1345, 1348–1350,
\textsc . 86, 87, 175, 189, 207	732, 734, 738, 740,	1352, 1356, 1362,
\thefield 625,	748, 750, 754, 756,	1365, 1368, 1374,
637, 833, 836, 898,	762, 763, 766, 767,	1375, 1378, 1379,
901, 961, 964, 2553,	770–772, 774, 778,	1403, 1405, 1416,
2632, 2640, 2659,	789, 793, 795, 803,	1420, 1422, 1428,
2671, 2679, 2680, 2708	805, 811, 812, 815,	1430, 1433, 1434,
\togglefalse	816, 820–822, 824,	1437, 1438, 1446,
. 630, 631, 819, 884,	828, 830, 832, 835,	1452, 1455, 1456,
947, 1617, 1680, 1789,	838, 841, 843, 845,	1459, 1460, 1488,
2000, 2577, 2686, 2687	851, 855, 862, 868,	1510, 1512, 1515–1517,
\toggletrue	870, 876, 877, 880,	1519, 1521, 1524, 1527,
89, 90, 2634, 2653, 2665	881, 885–887, 889,	1528, 1533, 1546,
	893, 895, 897, 900,	1548, 1554, 1556,
U	903, 906, 908, 914,	1562, 1563, 1566,
\undef 1732,	918, 925, 931, 933,	1567, 1628, 1633,
1755, 1857, 1877, 1963,	939, 940, 943, 944,	1635, 1636, 1642,
1985, 2031, 2050,	948–950, 952, 956,	1647, 1649, 1650,
2063, 2077, 2264,	958, 960, 963, 966,	1718, 1720, 1730,
2267, 2270, 2342,	969, 971, 973, 977,	1733, 1735, 1738,
2343, 2346, 2347,	983, 990, 996, 998,	1740, 1747, 1751, 1752,
2350, 2351, 2389, 2433	1004, 1005, 1008,	1756, 1758, 1761, 1766,
\unspace 635, 636,	1009, 1012–1014,	1768, 1774, 1779, 1781,
670, 721, 761, 810,	1016, 1020, 1022,	1845, 1847, 1855,
875, 938, 1003, 1053,	1026, 1036, 1038,	1858, 1860, 1863,
1091, 1131, 1172, 1204,	1046, 1048, 1054,	1865, 1872, 1876,
1255, 1299, 1339,	1055, 1058, 1059,	1878, 1879, 1881,
1373, 1561, 2137, 2185	1062–1064, 1066,	1886, 1891, 1893,
\uppercase	1070, 1072, 1082,	1899, 1904, 1906,
\url 155	1084, 1086, 1092,	1949, 1951, 1961,
\usebibmacro .. 101, 102,	1093, 1096, 1097,	1964, 1966, 1968,
105, 107–109, 221,	1100–1102, 1104,	1970, 1977, 1981,
223, 225, 287, 289,	1108, 1110, 1118, 1121,	1982, 1986, 1988,
290, 292, 306, 308,	1124, 1126, 1132, 1133,	2004, 2005, 2011,
310, 317, 325, 327,	1136, 1137, 1140–1142,	2012, 2022, 2029,
328, 334, 337, 340,	1144, 1148, 1159, 1163,	2030, 2034, 2036,
347, 349, 357, 359,	1165, 1167, 1173, 1174,	2043, 2047, 2048,
398, 405, 407, 409,	1177, 1178, 1181–1183,	2062, 2066, 2075,
413, 421, 425, 427,	1185, 1189, 1197, 1199,	2085, 2091, 2092,
432, 434, 436, 444,	1205, 1206, 1209,	2095–2097, 2099,
447, 473, 475, 477,	1210, 1213–1215, 1217,	2103, 2105, 2111, 2115,
481, 483, 485, 489,	1221, 1223, 1232,	2122, 2130, 2132,
491, 493, 526, 535,	1238, 1240, 1248,	2138, 2139, 2142,

2145–2147,	2149,	2443,	2470,	2472,		V
2153,	2164,	2168,	2473,	2478,	2480,	\value 99, 507,
2170,	2178,	2180,	2484,	2489–2491,		510, 1157, 1630–1632,
2186,	2187,	2190,	2494,	2497–2499,		1644–1646, 1674,
2204,	2214,	2221,	2502,	2507,	2511,	1675, 1763–1765,
2246,	2249,	2250,	2516,	2520,	2525,	1776–1778, 1888–
2252,	2254,	2259,	2528,	2531–2533,		1890, 1901–1903,
2260,	2281–2283,		2535,	2539,	2546,	2195–2197, 2210–
2288,	2289,	2303,	2549,	2555,	2608,	2212, 2245, 2262,
2306,	2309–2311,		2611,	2612,	2614,	2302, 2328, 2340,
2355,	2358–2360,		2616,	2624–2626,		2370, 2381, 2396,
2362,	2363,	2372,	2638,	2644,	2652,	2407, 2417, 2444,
2374,	2379,	2383,	2660,	2664,	2672,	2476, 2581, 2585,
2385,	2387,	2388,	2673,	2684,	2685,	2592, 2596, 2607, 2688
2392,	2397–2399,		2691–2695,	2697–		\volnumpunct
2402,	2403,	2408–	2699,	2701,	2703, 114, 363, 370, 375
2412,	2418,	2422,				
2423,	2427,	2429,				Y
2430,	2432,	2434,	\usedriver	618,		\yeartitle
			2551,	2655,	2667,	. 1797, 1799, 1807, 1829